

## UNI-T®

### UT07 Series Socket Testers



● UT07A-AU



● UT07B-AU



● UT07A-EU



● UT07B-EU



● UT07A-UK

● UT07A-IND

● UT07B-IND



● UT07D-IND  
(16A socket)

## SPECIFICATIONS

	UT07A-AU	UT07B-AU	UT07A-UK	UT07A-IND	UT07B-IND	UT07D-IND	UT07A-EU	UT07B-EU
Operating voltage	240V		230V	220V			230V	
Operating current	<18mA						<18mA	
Operating frequency	50Hz~60Hz			50Hz			50Hz~60Hz	
RCD	—	~30mA	—		~30mA	—		~30mA
Indications	Correct						OK, leakage test passed	
	Missing earth						OK	
	Live earth reverse						Missing earth	
	Live neutral reverse						Missing live	
	Missing neutral						Missing neutral	
	—						Live earth reverse	
—						Live earth reverse and missing earth		

## GENERAL CHARACTERISTICS

Product color	Red and grey
Product net weight	UT07A-AU/UT07B-AU: 58g; UT07A-UK/UT07A-IND: 64g; UT07B-IND: 65.5g; UT07D-IND: 72g; UT07A-EU: 79g; UT07B-EU: 80.5g
Product size	UT07A-UK/UT07A-AU/UT07B-AU: 65mm x 65mm x 40mm UT07A-IND/UT07B-IND/UT07D-IND/UT07A-EU/UT07B-EU: 65mm x 65mm x 61mm
Standard individual packing	Blister, English manual
Standard quantity per carton	UT07A-AU/UT07B-AU/UT07A-IND/UT07B-IND/UT07D-IND/UT07A-EU/UT07B-EU: 48pcs; UT07A-UK: 60pcs
Standard carton measurement	430mm x 330mm x 365mm (0.052 CBM per standard carton)
Standard carton gross weight	UT07A-AU/UT07B-AU: 3.9kg; UT07A-UK: 6.5kg; UT07A-IND/UT07B-IND/UT07D-IND: 6.8kg; UT07A-EU: 5.8kg; UT07B-EU: 5.4kg