

Нивелир Sola лазерен линеен с 3 лъча 25 м, 0.2 мм/м, Atlas Green



Ташев-Галвинг
www.tashev-galving.com



ATLAS GREEN

Model

ATLAS GREEN

Technical details:

Item description	Line laser
Dimension	125 x 123 x 204 mm
Levelling	self-levelling
Measuring tolerance	±0.20 mm/m
Self-levelling range	±3°
Application range without handheld receiver (radius)	25 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)
Tripod adapter	5/8"
Protection class	IP54
Power supply	4 x 1.5 V (AA) batteries
Operating time (at 20 °C)	6.5 hrs (all diodes)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 5.0 mW
Wavelength	510 - 525 nm

CHARACTERISTICS:

- High accuracy
- Very visible laser lines, individually switchable
- Switchable inclination function
- Rotatable through flexible 360° plumbing point for a quick and easy alignment. Plumbing point is always on the rail edge.
- Permanent pulse function enables use of the optional REC LGDO receiver in difficult visibility conditions
- REAL GREEN technology - Real. Improved. Visible.

APPLICATIONS:

- Horizontal levelling
- Inclination manually
- Vertical levelling
- 90° alignment
- Plumbing
- Aligning

Included accessory:

- 4 x 1.5 V (AA) batteries
- LB GREEN
- TA 1/4" ATLAS GREEN
- TA 5/8" ATLAS GREEN



Продукт: [Нивелир Sola лазерен линеен с 3 лъча 25 м, 0.2 мм/м, Atlas Green](#)

Категория: [Нивелири](#)

Бранд: [Sola](#)

Категория бранд: [Нивелир Sola](#)