


Нивелир Sola лазерен ротационен с приемник 300 м, 0.1 мм/м, EVO 360



ТашевТашев
www.tashev.com



CHARACTERISTICS:

- For use in horizontal or vertical operation
- Particularly easy and safe operation
- even for less experienced users
- Robust: IP66 protection and a drop resistance rating from one meter onto concrete
- Very high accuracy
- Plumbing point for marking out right angles
- Leveling time < 20 s thanks to servo motors

APPLICATIONS:

- Horizontal leveling
- Vertical leveling

EVO 360

Model

EVO 360

Technical details:

Item description	Horizontal/vertical rotation laser
Dimensions	179 x 143 x 211 mm
Leveling	automatic
Measuring tolerance	±0.10 mm/m
Self-leveling range	±5°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	300 m*
Operating temperature	-10°C to +50 °C
Rotation speed	600 rpm
Tripod adapter	5/8"
Protection class	IP66
Power supply	2 x 3.6-V Li-ion battery (3450 mAh)
Operating time (at 20°C, 68°F)	40 hrs
Laser class	2M, DIN EN 60825-1:2014+A1:2017
Output power	< 1.0 mW
Wavelength	635–650 nm

Included accessory:

- REC RRD1
- Rechargeable battery cell 18650
- Charger
- Power plug
- EVO 360 case



Продукт: [Нивелир Sola лазерен ротационен с приемник 300 м, 0.1 мм/м, EVO 360](#)

Категория: [Нивелири](#)

Бранд: [Марка Sola](#)

Категория бранд: [Нивелир Sola](#)