

# Sound Level Meters, Lux Meters, Anemometer



## Electr. Digital Sound Level Meter

- for sound and noise measurements acc. to the international directives whether in industry, craft, or housekeeping
- useful device for air-conditioning, aviation industry, environmental technology
- with self-calibration
- rugged, polyamide housing material
- On/Off button, data memory for 4700 measurements, slow-/fast-button, clock- and calendar indicator
- with tripod mounting screw on the rear side, autom. power off
- large LCD display, 4-digit, with clear reading, battery indicator
- frequency range 31.5 Hz ~ 8.5 KHz, A/C frequency weighting select switch, AC/DC out put
- bar graph indicator with 50 dB scale, 1 dB step, with pre-select of min/max.-value
- microphone 1/2 inch, electret condenser-microphone, with detachable foam ball for outside measuring
- storage temperature -20°C ~ +70°C, operation temperature 0°C ~ +45°C, DC 6 V input port, AC analog output port
- incl. 4x 1.5 V battery (type AA, art.-no. 609282), USB data cable, software, with operation manual



foam ball  
removable



side

### Option

- charging by power supply possible, only when using rechargeable batteries!



ART NO

641106

level range  
dBA / dBC

40-80 / 50-100 / 60-110 / 80-130

dB

0.1

max.  
dB

± 1.5

linearity range  
dB

50

mm

220 x 80 x 35

KG

0.235

CC

inclusive