


Laserliner®

HYBRID AND ROTARY LASERS

HIGH VISIBILITY

Interior finishing work, above and below ground construction

Quadrum DigiPlus 410 S



- 2-axis inclination laser**
- 6° self-levelling range, accuracy 0.075 mm / m
 - Deviation from the horizontal plane can set digitally in X and Y axes.
 - Laser modes: spot, scan, rotary and hand receiver mode
 - High maximum speed of 600 rpm
 - Large illuminated LCD
 - The laser modes of the rotary laser can be controlled with the remote control from up to 40 m.
 - The 4 IR receiving diodes allow this instrument to be remotely operated from all sides.
 - Laser receiver range up to 400 m radius

Inclusive: Quadrum DigiPlus, SensoLite 410, universal mount, remote control, rechargeable battery, battery compartment, power supply/battery charger, carrying case, batteries



Clearly arranged, illuminated LCD
All operating modes are shown on the large LC display. This makes it easy and straightforward to set up the device. Direct read-off of set inclination.



ORDER NO.	EAN-CODE	PU
053.300A	4 021563 682270	1

Quadrum DigiPlus 400 Pro S

NEW




- 2-axis inclination laser**
- Product description same as Quadrum DigiPlus 410 S
 - With SensoMaster 400 Pro instead of SensoLite 410

Inclusive: Quadrum DigiPlus, SensoMaster 400 Pro, universal mount, remote control, rechargeable battery, battery compartment, power supply/battery charger, batteries, carrying case, batteries

ORDER NO.	EAN-CODE	PU
053.350A	4 021563 708956	1



Centurium Express G 410 S



- Fully automatic rotary laser with green DLD-laser technology**
- With DLD technology for a clearly visible laser beam
 - 4° self-levelling range, accuracy 0.075 mm / m
 - Laser modes: spot, scan, rotary and hand receiver mode
 - All functions of the rotary laser can be controlled with the remote control from up to 40 m.
 - The 4 IR receiving diodes allow this instrument to be remotely operated from all sides.
 - Extremely high speed of max. 800 rpm for fast results in express hand-held receiver mode
 - AntiShake function for quick set-up on ground with slight vibrations and in strong wind
 - Laser receiver range up to 400 m radius
 - Green laser technology with 0°C...50°C temperature range

Inclusive: Centurium Express G, SensoLite 410, universal mount, remote control, rechargeable battery, battery compartment, power supply/battery charger, batteries, complete in the L-BOXX 238



ORDER NO.	EAN-CODE	PU
056.500L	4 021563 685301	1



* Approx. 6 times brighter than a typical red 630 - 660 nm laser