Laserliner®

Laser distance measurement

DistanceMaster Compact Pro

MeasureNote App

2 Positions

max. 50 m

Laser distance meter with Bluetooth interface and angle function
– Measuring range, internal 0.1 to 50 m*
– Measuring precision of ± 2 mm (typical)*
– The area and volume functions permit the acquisition of room sizes, for example to calculate material quantities
– Angle function 1 + 2 +3**, Min./Max. continuous measurement
– Bluetooth interface for measurement data transfer
– 360° inclination sensor for determining the horizontal and vertical distance
– With storage options
– Illuminated 3-line colour LC display
– Sturdy, ergonomically designed housing

*   See operating instructions for specific measuring ranges and accuracies
** In combination with 360° inclination sensor

Inclusive: DistanceMaster Compact Pro, softbag, batteries

ORDER NO.	EAN-CODE	PU
080.937A	4 021563 692903	2

Laser 650 nm | 2 | SPEED SHUTTER | Bluetooth® | 2 x AAA | SOFT

DistanceMaster

max. 100 m

4 Positions

Professional laser distance meter
– Measuring range 0.05 to 100 m*
– High measuring precision of ±1.5 mm (typical)*
– Features distance, surface and volume calculation, Pythagoras 1+2, Min./Max. continuous measurement and plus/minus function
– With versatile calculation and memory functions
– Reference mode for easy transfer of lengths
– 1/4" threaded connection
– Measure out of a corner with the screw-on measuring prod

* See operating instructions for specific measuring ranges and accuracies

Inclusive: DistanceMaster, fold-out pin, softbag, batteries

ORDER NO.	EAN-CODE	PU
080.946A	4 021563 680634	2

Laser 635 nm | 2 | SPEED SHUTTER | 1/4" | 2 x AAA | SOFT

DistanceMaster Vision

max. 80 m

4 Positions

Laser distance meter with camera function
– Measuring range 0.05 to 80 m*
– Measuring precision of ± 2 mm (typical)*
– The area and volume functions permit the acquisition of room sizes, for example to calculate material quantities
– Simple assessment of room perimeter with the addition and subtraction functions
– Pythagoras 1 + 2 + 3, angle function 1**, Min./Max continuous measurement
– The wall surface function automatically adds up surfaces by measuring the lengths of walls as well as their height once.
– Stake out function for marking off defined lengths
– Camera with digital zoom
– Digital bubble level is used to align the measuring device
– Timer function to automatically trigger
– 360° inclination sensor for determining the

horizontal and vertical distance
– Micro USB port for charging batteries
– 1/4" threaded connection
– Illuminated colour LC display
– Sturdy, ergonomically designed housing

*   See operating instructions for specific measuring ranges and accuracies
** In combination with 360° inclination sensor

Inclusive: DistanceMaster Vision, USB charging cable, softbag, rechargeable batteries, carrying case

ORDER NO.	EAN-CODE	PU
080.980A	4 021563 703661	2

Laser 635 nm | 2 | 1/4" | NiMH Battery | HARD

RollPilot S6

Measuring wheel for use on straight lines and curves
– Mechanical measuring wheel: Distances up to 9,999.9 m
– Large, easy to read display with additional fine scale (1 - 9 cm) for precise measurement.
– Addition when wheels are turning forwards and subtraction when backwards
– Wall-to-wall function: The compact design enables direct measurement from wall to wall.
– Brake and zero setting directly on handle
– Non-wearing cardanic scale drive
– Accuracy ± 0.1%
– Metering wheel with 0.5 m circumference

Inclusive: RollPilot S6, softbag

ORDER NO.	EAN-CODE	PU
075.008A	4 021563 692521	2

SOFT

RollPilot D12

Electronic measuring wheel for use on straight lines and curves
– Electronic measuring wheel delivers measured values accurate to the centimetre when measuring distances of up to 9,999.99 m.
– Easy-to-read, illuminated LC display directly on the handle.
– Addition when wheels are turning forwards and subtraction when backwards
– Hold function for holding the measured value
– Measured value memory for 5 entries
– The moving pointer shows the exact start and end positions.
– Folding design and softbag for easy transport
– Accuracy ± 0.1%
– Metering wheel with 1 m circumference

Inclusive: RollPilot D12, softbag, battery

ORDER NO.	EAN-CODE	PU
075.006A	4 021563 680818	1

9 V | SOFT