

HIT-1200

R-V.1.01

JUN2016

Ref.: 26931 Ref.: 19962 – With bag*

Robust and accurate manual tile cutter.

For intensive cutting of ceramic tiles, stoneware and porcelain tiles.

FUNCTIONAL CHARACTERISTICS

With high performance movable breaker.

Set of sliders with self-lubricating friction bearing for greater ACOURACY and COMFORT during scoring.

Oose structure, extruded aluminium base for a greater RIGIDITY and cutting CAPACITY.

Solid, chromed, rectified and calibrated steel guides with anti-corrosion treatment of \emptyset 20 mm for a better resistance to flexion.

With lateral stop for repetitive and 45° cuts.

Equipped with 4 supplementary arms for large-sized tiles.

Bi-material handle for a better COMFORT.

Wide range of scoring wheels to suit different materials (Ø 6, 8, 10, 18 and 22 mm.), includes 8 mm. scoring wheel.





HIT-1200

R-V.1.01

JUN2016

TECHNICAL SPECIFICATIONS

- Outting length: 120 cm.
- Maximum size for diagonal cut: 84.5x84.5 cm.
- Thickness of cut: 3 to 15 mm.
- Weight: 13 kg.
- Dimensions: 144x26x26 cm
- * Available with practical transport shoulder bag (Ref.: 19962).



PACKAGING

Unitary carton box with RUBI flexography.

Unitary gross weight: 13.85 kg. (14.71 kg ref. 19962 with bag).

Sales unit: 1 unit (bulk box).

Units per pallet: 24 units

Pallet dimensions: 144x100x102 cm.

Pallet weight: 358 kg. (380 kg ref. 19962 with bag).

Is the customer's responsibility to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate. Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products. All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge. Data and the own technical sheet can be changed without prior notice.