

Технически характеристики

Борщанга PG за метал ф 27-104 мм





ref.	description	RPM	pack.
214.00	hexagonal shank Ø 8 mm - pilot drill Ø 6 mm - to drill from 20 mm to 123 mm - complete with HSS drill Ø 6 mm - wrench - 5 mm HSS cutting tool with 5% cobalt	250	5
215.00	hexagonal shank Ø 12 mm - pilot drill Ø 10 mm - to drill from 25 mm to 217 mm - complete with HSS drill Ø 10 mm - wrench - 6 mm HSS cutting tool with 5% cobalt	250	5
216.00	hexagonal shank Ø 8 mm - pilot drill Ø 4 mm - to drill from 27 mm to 104 mm - complete with HSS drill Ø 5 mm - wrench - Ø 5 mm HSS cutting tool with 5% cobalt	250	5

1.50	REPLAC	EMENT HSS CUTTING TOOL		
	ref.		description	pac
	214.10	5 mm for ref. 214.00	THE PROPERTY OF THE PROPERTY O	5
	215.10	6 mm for ref. 215.00		. 5
	216.10	Ø 5 mm for ref. 216.00		5
щанга PG з оркорони за анд: <u>Борща</u>	строите	ф 27-104 мм лни материали	2 '62' 0 /	
		B	0	
	4	(0,0)		
	2			
	80	NO SOLO		
\ \tag{2}		N. S.		
70		N. S.		
70				
70	MILLION			
70	White Co.			
	William			
70	MALLOS			

Продукт: Борщанга PG за метал ф 27-104 мм Категория: Боркорони за строителни материали

Бранд: PG

Категория бранд: <u>Борщанга PG</u>