



Split hole punch TriCut™ for sheet steel (S235)

- 1 With 3-fold split
- 2 With UNF fine thread
- 3 With 4 crosshair markings for simple, central alignment



"The max. material thickness for which a hole punch can be used always depends on the screw and draw bolts used."

Usable up to a material thickness of:

- 3.0 mm sheet steel with 3/4" (19.0 mm) screw or draw bolt
- 2.0 mm sheet steel with 3/8" (9.5 mm) screw or draw bolt
- 1.5 mm steel sheet with M6 (6.0 mm) screw or draw bolt

Split hole punch TriCut™ - sets



All sets are supplied in heavy-duty practical plastic cases.

Ø mm	12.5	15.2	16.2	18.6	19.0	20.4	22.5	25.4	28.3	30.5	31.7	32.5	34.6	37.0	38.0	40.5	43.2	47.0	49.6	50.5	54.0	60.0	61.5	63.5
Ø metric	M12	-	M16	-	-	M20	-	M25	-	-	-	M32	-	-	-	M40	-	-	-	M50	-	-	-	M63
Ø PG	7	9	-	11	-	13	16	-	21	-	-	-	-	29	-	-	-	36	-	-	42	48	-	-
Ø Inch	1/2"	-	-	-	3/4"	-	7/8"	1"	-	1-7/32"	1-1/4"	-	-	-	1-1/2"	-	1-11/16"	-	1-15/16"	-	2-1/8"	-	2-3/8"	2-1/2"
Ø Conduit	-	-	-	-	-	-	1/2"	3/4"	-	-	-	-	1"	-	-	-	1 1/4"	-	1 1/2"	-	-	-	2"	-

Prod.-No.	12.5	15.2	16.2	18.6	19.0	20.4	22.5	25.4	28.3	30.5	31.7	32.5	34.6	37.0	38.0	40.5	43.2	47.0	49.6	50.5	54.0	60.0	61.5	63.5		
01762			•			•		•				•				•										
01757			•			•		•				•				•				•					•	
01760							•		•				•				•		•				•			
01761	•				•			•			•				•					•						
01754	•		•			•		•			•				•					•						
+ 1 ball bearing screw Ø 6.0 x 40.0 mm, 1 ball bearing screw Ø 9.5 x 50.0 mm, 1 ball bearing screw Ø 19.0 x 55.0 mm, 1 pre-drill HSS Ø 10.0 mm, 1 can lubricating paste																										
01755			•			•		•				•				•				•					•	
+ 2 ball bearing screws Ø 9.5 x 50.0 mm, 1 ball bearing screw Ø 19.0 x 55.0 mm, 1 ball bearing screw Ø 19.0 x 75.0 mm, 1 pre-drill HSS Ø 10.0 mm, 1 can lubricating paste																										
01750		•		•		•	•			•																
+ 2 ball bearing screws Ø 9.5 x 50.0 mm, 1 pre-drill HSS Ø 10.0 mm, 1 tube lubricating paste																										
01751		•		•		•	•			•	•				•					•			•	•		
+ 2 ball bearing screws Ø 9.5 x 50.0 mm, 1 ball bearing screw Ø 19.0 x 55.0 mm, 1 ball bearing screw Ø 19.0 x 75.0 mm, 1 pre-drill HSS Ø 10.0 mm, 1 can lubricating paste																										

Ø in mm	Max. Material thickness in mm (S235)	Size Metric	Size PG	Size Inch		Size Conduit & Pipe Size	 Punches and dies, draw bolt with ball bearing	 Punches and dies	 matching draw bolt	 matching draw bolt with ball bearing	Prod.-No.			
12.5	1.5	M 12	7	1/2"	0,500	-	01674	01770	02022	01334				
15.2	2.0	-	9	-	0,598	-	01680	01771						
16.2	2.0	M 16	-	-	0,638	-	01683	01772						
18.6	2.0	-	11	-	0,732	-	01686	01773						
20.4	2.0	M 20	13	-	0,803	-	01689	01774	02003	01339				
22.5	2.0	-	16	7/8"	0,886	1/2"	01692	01775						
25.4	2.0	M 25	-	1"	1,000	-	01695	01776						
28.3	2.0	-	21	-	1,114	3/4"	01698	01777						
28.3	3.0	-	21	-	1,114	3/4"	01701	01778	02002	01340				
30.5	2.0	-	-	1-7/32"	1,201	-	01703	01779	02003	01339				
32.5	3.0	M 32	-	-	1,280	-	01708	01780						
34.6	3.0	-	-	1-11/32"	1,362	1"	01711	01788						01340
37.0	3.0	-	29	-	1,457	-	01713	01781						
40.5	3.0	M 40	-	-	1,594	-	01715	01782						
43.2	3.0	-	-	1-11/16"	1,701	1 1/4"	01718	01789						
47.0	3.0	-	36	-	1,850	-	01720	01783						
49.6	3.0	-	-	1-15/16"	1,953	1 1/2"	01723	01790	02002					
50.5	3.0	M 50	-	-	1,988	-	01736	01784						01341
54.0	3.0	-	42	2-1/8"	2,126	-	01727	01785						
60.0	3.0	-	48	-	2,362	-	01729	01786						
61.5	3.0	-	-	2-3/8"	2,421	2"	01732	01791						
63.5	3.0	M 63	-	2-1/2"	2,500	-	01739	01787						