

L-185 AA
COMPRESSED AIR 20 BAR (300 PSI) - STANDARD
DUTY
EXCEEDS DIN 20018/1



TUBE	BLACK SYNTHETIC ELASTOMER - OIL MIST RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK OR RED SYNTHETIC ELASTOMER WITH LONGITUDINAL YELLOW STRIPES - ABRASION AND OZONE RESISTANT
APPLICATION	COMPRESSED AIR AND GENERAL INDUSTRIAL APPLICATIONS.
SAFETY FACTOR	3:1
TEMPERATURE	-10°C +60°C (+14°F +140°F)
BRAND TEXT	ALFAGOMMA - ITALY - L-185 - 20 BAR (300 PSI) - AIR - dia mm -ggga
BRAND TYPE	EMBOSSSED
APPROVALS	
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP Vac. psi %	BR mm	Available Length m	Stock Length m
185AA0061311Y0	6	1/4	13	3,5	145	20	300	48	100	100
185AA0081511Y0	8	5/16	15	3,5	175	20	300	64	100	100
185AA0101711Y0	10	3/8	17	3,5	205	20	300	80	100	100
185AA0132111Y0	13	1/2	21	4	300	20	300	104	40/100	40/100
185AA0162511Y0	16	5/8	25	4,5	395	20	300	128	100	100
185AA0192911YZ	19	3/4	29	5	465	20	300	152	40/50/100	40/50/100
185AA0253611Y0	25	1"	35	5	640	20	300	200	40/50/100	40/50/100

Ташев Галвинг ООД
www.tashevgalving.com