

FKD-R



Cooling - EPDM - 6 bar

Application:

Cooling hose for combustion engines.

Feature:

Good resistance to ageing under the influence of hot water, hot air and anti-freezing agents.

Ozone resistant.

Temperature range:

-40°C / +120°C.

Safety factor:

2,5 : 1

Tube:

EPDM, black, smooth.

Reinforcement:

Textile spiral.

Cover:

EPDM, black, resistant to ozone and weather, smooth.

Marking:

continuous inkjet, white letters:

"SEMPERIT (S) FKD Kühlwasser/Cooling Water ID x WT
>EPDM/PES/EPDM< XQ/YYYY -40°C / +120°C MADE IN EU
//////"



Article number	Internal-Ø in		Wall width	External-Ø	Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
	mm	inch	in mm						
68201 1035	10,0	3/8	3,5	17,0	6	2	60	0,22	50
68201 1235	12,0		3,5	19,0	6	2	70	0,25	50
68201 1236	12,5	1/2	3,5	19,5	6	2	75	0,26	50
68201 1335	13,0		3,5	20,0	6	2	80	0,27	50
68201 1435	14,0	9/16	3,5	21,0	6	2	85	0,28	50
68201 1535	15,0		3,5	22,0	6	2	90	0,31	50
68201 1635	16,0	5/8	3,5	23,0	6	2	95	0,32	50
68201 1835	18,0		3,5	25,0	6	2	110	0,34	50
68201 1935	19,0	3/4	3,5	26,0	6	2	115	0,35	50
68201 2035	20,0		3,5	27,0	6	2	120	0,38	50
68201 2235	22,0	7/8	3,5	29,0	6	2	135	0,39	50
68201 2535	25,0	1	3,5	32,0	6	2	150	0,46	50
68201 3255	32,0	1 1/4	5,5	43,0	6	2	195	0,96	50