


**Маркуч Semperit за вода под налягане каучук, 33 мм, 25 мм,
10 bar, PLW10**





Air/Water - 10 bar

SPECIFICATIONS

Application	A flexible air and water hose for use in industry, commerce and on construction sites.
Temperature range	-30°C / +70°C.
Safety factor	3 : 1
Tube	Synthetic rubber, black, suitable for oil-laden air, smooth.
Reinforcement	Textile spiral (DN > 32 wrapped).
Cover	Synthetic rubber, black, resistant to ozone and weather, smooth (DN > 32 cloth impression).
Marking	continuous inkjet, white letters: "SEMPERIT (S) PLW10 Luft/Wasser Air/Water WP 10 bar/BP 30 bar DN MADE IN EU //////////////". DN >32 continuous mylartape, white letters: "SEMPERIT (S) PLW10 Luft/Wasser Air/Water WP 10 bar/BP 30 bar MADE IN EU //////////////".
Notice	Larger dimensions available on request.

TECHNICAL DETAILS

Article number	Internal-Ø		Wall width	External-Ø		Work. pressure (max.)	Number of inserts	Bending radius (min.)	Weight approx.	Coil length (max.)
	mm	inch		mm	mm					
68101 0630	6,0	1/4	3,0	12,0	10	2	60	0,13	50	
68101 0835	8,0	5/16	3,5	15,0	10	2	80	0,19	50	
68101 1035	10,0	3/8	3,5	17,0	10	2	100	0,22	50	
68101 1335	13,0	1/2	3,5	20,0	10	2	130	0,24	50	
68101 1635	16,0	5/8	3,5	23,0	10	2	160	0,28	50	
68101 1935	19,0	3/4	3,5	26,0	10	2	190	0,33	50	
68101 2540	25,0	1	4,0	33,0	10	2	250	0,48	50	
68101 3255	32,0	1 1/2	5,5	43,0	10	2	320	1,09	50	
48411 3860	38,0		6,0	50,0	10	2	380	1,15	40	
48411 5060	50,0		6,0	62,0	10	2	500	1,35	40	
48411 6370	63,5	2 1/2	7,0	77,5	10	4	630	2,05	40	
48411 7580	75,0		8,0	91,0	10	4	750	2,60	40	

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website (<https://hoses.semperitgroup.com/>) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (<https://hoses.semperitgroup.com/>) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications

Продукт: [Маркуч Semperit за вода под налягане каучук, 33 мм, 25 мм, 10 бар, PLW10](#)

Категория: [Маркучи технически](#)

Бранд: [Semperit](#)

Категория бранд: [Маркуч Semperit](#)