



580 OIL FUEL

Inwendig NBR Kleur Zwart Uitwendig CHEMIVIC Kleur Zwart	Innen NBR Farbe Schwarz Außen CHEMIVIC Farbe Schwarz	Inside NBR Colour Black Outside CHEMIVIC Colour Black
Brandstofslang voor diesel- en benzine voertuigen	Kraftstoffschlauch für Diesel und Benzinfahrzeuge	Oil and fuelhose for petroleum and diesel vehicle applications
- Inwendig Chemigum, bestendig tegen benzine, diesel, petroleum, E5/E10, B5 - Uitwendig bestendig tegen diesel en benzine, hittebestendig max. 100 °C - Binnenwand compound conform SAE 30R7 en RMA Class A - Niet geschikt voor biodiesel B100 of hogere concentraties ethanol blends - Niet geschikt voor hogedruk injectie leidingen - Toleranties maatvoering conform ISO1307	- Seele Chemigum, beständig gegen Benzin, Diesel, Petroleum, E5/E10 und B5 - Decke beständig gegen Öl- und Diesel spuren, Wärmebeständigkeit max. 100 °C - Mischung der Seele entspricht SAE30R7, RMA Class A - Nicht geeignet für Biodiesel B100 oder höher konzentrierte Ethanol blends - Nicht geeignet für Hochdruck Injektionsleitungen - Fertigungstoleranzen nach ISO1307	- Smooth Chemigum tube, resistant to petroleum based fuels, diesel fuel, gasoline E5/E10 and B5 - Cover is oil, fuel and heat resistant, cover heat exposure max. 100 °C - Tube compound meets SAE 30R7 RMA class A requirements - Not suitable for B100 fuels or higher ethanol blends - Do not use for high pressure line on fuel injection engines - Manufacturing tolerances according ISO1307

Array

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
3.2	8.5	25.0	0	65	10
4.0	9.3	32.0	0	73	10
5.0	10.5	40.0	0	88	10
6.0	12.4	48.0	0	120	10
8.0	14.3	64.0	0	145	10
9.5	15.9	80.0	0	170	10
12.0	19.1	100	0	230	10

Normen / Standards

ISO 1307 - SAE 30R7 - RMA CLASS A

Temperatuurbereik (Zie medium)
Temperatuurbereich (siehe Medium)
Temperature range (see media)
-40 °C +93 °C

Werkdruk Barstdruk
Betriebsdruck Platzdruck
Working pressure Burst pressure
10 bar 30 bar

Markering / Markierung / Branding:
CONTINENTAL CONTITECH 580-216
FUEL/OIL WP 10 BAR / BP 30 BAR ID MM
MADE IN USA

Lengten / Längen / Lengths

50 m

Kan per diameter verschillen / Kann je nach Durchmesser variieren / Can vary per diameter