97

Self-adjusting crimping pliers for end sleeves (ferrules) with rotating crimp head

- Crimp head can be freely rotated 360°, with 8 locking positions
- ► Square crimp profile, high capacity range of 0.14 to 16 mm²
- ▶ End sleeves (ferrules) can be crimped from almost any working position
- >Crimping pliers adjust automatically to different cross-sections
- >Crimp opening accessible from both sides, extra-long end sleeves can be fed in
- >Crimping of twin end sleeves (ferrules) up to 2 x 6 mm² possible
- >Repetitive, high crimping quality due to integral lock (self-releasing mechanism)
- >Light and handy tool, manual force reinforced by toggle lever mechanism
- >Chrome vanadium electric steel in special quality, oil-hardened






Crimp head can be rotated 360° for optimal accessibility, even in confined spaces



Twin end sleeves (ferrules) up to 2 x 6 mm² can be crimped without adjustment



Crimp end sleeves (ferrules) fully automatically within the capacity range of 0.14 to 16 mm²



Uniquely flexible: connectors can be inserted in the rotatable crimp head from almost any position





	EAN	←→				7,7
Article No.	4003773-	mm	Capacity mm ²	AWG	Number of crimping positions	g
97 53 18	082729	200	0.14 - 16	26 - 5	1	478
97 53 18 SB N	082736	200	0.14 - 16	26 - 5	1	478