

# Injection polyurethane wheels, polyamide 6 centre, fixed bracket type NLX



## Wheel description

Injection polyurethane tread; hardness 60 Shore D. Polyamide 6 centre.

## Plain bearing bore or stainless steel roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains stainless steel cylindrical roller bearings with polyamide







## Stainless steel axle


Axle composed of ground AISI 304 stainless steel bush, with stainless steel bolt according to UNI EN 24017 and stainless steel nut according to UNI EN 24032.







## Fixed bracket type NLX

Fixed bracket type NLX. The fork is made of AISI 304 stainless steel.



	80	30	107	100x85	80x60	9	120	0,35	*	605101
	100	30	128	100x85	80x60	9	170	0,40	*	605102
	125	35	156	100x85	80x60	9	220	0,64	*	605103
	150	35	182	100x85	80x60	9	220	0,81	*	605104
	150	45	194	140x110	105x80	11	300	1,33	*	605111
	200	50	240	140x110	105x80	11	300	1,74	*	605106



	80	30	107	100x85	80x60	9	120	0,38	*	605601
	100	30	128	100x85	80x60	9	170	0,41	*	605602
	125	35	156	100x85	80x60	9	220	0,66	*	605603
	150	35	182	100x85	80x60	9	220	0,83	*	605604
	150	45	194	140x110	105x80	11	300	1,38	*	605611
	200	50	240	140x110	105x80	11	300	1,79	*	605606