

Injection polyurethane wheels, polyamide 6 centre, swivel top plate bracket type NLX with front lock



Wheel description

Injection polyurethane tread; hardness 60 Shore D. Polyamide 6 centre.

Plain bearing bore or stainless steel roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains stainless steel cylindrical roller bearings with polyamide

Stainless steel axle

Axle composed of ground AISI 304 stainless steel bush, with stainless steel bolt according to UNI EN 24017 and stainless steel nut according to UNI EN 24032.

Swivel top plate bracket type NLX. The plate, the ball race ring and the fork are made of AISI 304 stainless steel; swivel actions: double ball greased race of AISI 304 stainless steel with dust protection seal made of polyethylene. The king pin is integral with top plate and duly rivetted. The front brake is necessary to lock wheel and top plate rotation.



	80	30	107	100x85	80x60	9	39	120	120	0,78	*	606701
	100	30	128	100x85	80x60	9	35	120	170	0,83	*	606702
	125	35	156	100x85	80x60	9	37	120	220	0,95	*	606703
	150	35	182	100x85	80x60	9	37	120	220	1,10	*	606704
	150	45	194	140x110	105x80	11	56	156	300	2,06	*	606711
	200	50	240	140x110	105x80	11	56	156	300	2,48	*	606706