

Injection polyurethane wheels, polyamide 6 centre, swivel bracket with bolt hole type NLX



Wheel description

Injection polyurethane tread; hardness 60 Shore D. Polyamide 6 centre.

Plain bearing bore or stainless steel roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains stainless steel cylindrical roller bearings with polyam







Stainless steel axle

Axle composed of ground AISI 304 stainless steel bush, with stainless steel bolt according to UNI EN 24017 and stainless steel nut according to UNI EN 24032.







Swivel bracket type NLX with bolt hole

Swivel bracket type NLX. The plate and fork are made of AISI 304 stainless steel; swivel actions: double ball greased race of AISI 304 stainless steel. The king pin is integral with top plate and duly rivetted.



	80	30	107	39	73	12	120	0,55	*	607901
	100	30	128	35	73	12	170	0,61	*	607902
	125	35	156	37	73	12	220	0,79	*	607903
	150	35	182	37	73	12	220	0,90	*	607904
	150	45	188	56	102	20	300	1,57	*	607911
	200	50	236	56	102	20	300	2,14	*	607906



	80	30	107	39	73	12	120	0,58	*	608001
	100	30	128	35	73	12	170	0,62	*	608002
	125	35	156	37	73	12	220	0,81	*	608003
	150	35	182	37	73	12	220	0,82	*	608004
	150	45	188	56	102	20	300	1,62	*	608011
	200	50	236	56	102	20	300	2,19	*	608006