

Non-marking rubber wheels, pressed steel discs, fixed bracket type NL



Wheel description

Standard non-marking rubber tread; hardness 80 Shore A.
Centre made of two riveted galvanized pressed steel discs.

Bush bearing bore or roller bearing bore

In the bush bearing bore, the hub contains a bush made of polyamide 6 with molybdenum disulphide to make it self-lubricating.

In the roller bearing bore, the bearing housing contains cylindrical roller bearings with polyamide 6 cage.

Axle


Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.

Fixed bracket type NL

Fixed bracket type NL. The fork is made of pressed steel zinc plated.



	80	25	107	100x85	80x60	9	65	0,49	*	235701
	100	30	128	100x85	80x60	9	80	0,62	*	235702
	125	37,5	156	100x85	80x60	9	130	0,92	*	235703
	140	37,5	176	100x85	80x60	9	150	0,93	*	235704
	150	40	182	100x85	80x60	9	170	1,04	*	235711
	160	40	199	140x110	105x80	11	180	2,07	*	235710
	200	50	240	140x110	105x80	11	230	2,89	*	235706



	80	25	107	100x85	80x60	9	65	0,51	*	235901
	100	30	128	100x85	80x60	9	80	0,65	*	235902
	125	37,5	156	100x85	80x60	9	130	0,95	*	235903
	140	37,5	176	100x85	80x60	9	150	0,96	*	235904
	150	40	182	100x85	80x60	9	170	1,07	*	235911
	160	40	199	140x110	105x80	11	180	2,13	*	235910
	200	50	240	140x110	105x80	11	230	3,05	*	235906