

Injection polyurethane wheels, polyamide 6 centre, fixed bracket type NLX



Wheel description

Injection polyurethane tread; hardness 60 Shore D.
Polyamide 6 centre.

Plain bearing bore or stainless steel roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains stainless steel cylindrical roller bearings with polyamide 6 cage.

Stainless steel axle


Axle composed of ground AISI 304 stainless steel bush, with stainless steel bolt according to UNI EN 24017 and stainless steel nut according to UNI EN 24032.

Fixed bracket type NLX

Fixed bracket type NLX. The fork is made of AISI 304 stainless steel.



	80	100	125	150	150	200
Wheel diameter (mm)	80	100	125	150	150	200
Wheel width (mm)	30	30	35	35	45	50
Wheel height (mm)	107	128	156	182	194	240
Wheel bore diameter (mm)	100x85	100x85	100x85	100x85	140x110	140x110
Wheel bore diameter (mm)	80x60	80x60	80x60	80x60	105x80	105x80
Wheel bore diameter (mm)	9	9	9	9	11	11
Wheel weight (kg)	120	170	220	220	300	300
Wheel weight (kg)	0,35	0,40	0,64	0,81	1,33	1,74
Wheel weight (kg)	*	*	*	*	*	*
Wheel weight (kg)	605101	605102	605103	605104	605111	605106



	80	100	125	150	150	200
Wheel diameter (mm)	80	100	125	150	150	200
Wheel width (mm)	30	30	35	35	45	50
Wheel height (mm)	107	128	156	182	194	240
Wheel bore diameter (mm)	100x85	100x85	100x85	100x85	140x110	140x110
Wheel bore diameter (mm)	80x60	80x60	80x60	80x60	105x80	105x80
Wheel bore diameter (mm)	9	9	9	9	11	11
Wheel weight (kg)	120	170	220	220	300	300
Wheel weight (kg)	0,38	0,41	0,66	0,83	1,38	1,79
Wheel weight (kg)	*	*	*	*	*	*
Wheel weight (kg)	605601	605602	605603	605604	605611	605606