




Grass Trimmer & Strimmers

Husqvarna 129LK

Available to buy online with exclusive
free products and free home delivery.
Direct from Husqvarna.

**AVAILABLE
TO BUY
ONLINE**

Trimmer 129LK is a multi-purpose tool that features a powerful 27cc engine and professional quality – combined with a focus on ease of use. It is easy to start thanks to Smart Start®, intuitive controls and the automatic stop return switch – a feature that automatically resets to the ON position for trouble-free starting. Apart from trimmer head, 129LK can easily be equipped with a number of other pro-quality tools: blower, pole saw, cultivator, hedge trimmer and edger, by changing the lower part of the shaft.

 Cylinder displacement	27.6 cm³
 Cutting width	43 cm
 Weight (excl. cutting equipment)	4.67 kg

Price includes:
Trimmer head T25
Combi guard 128L mfl.



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its design and features.



Intuitive controls

The choke and purge are easy to reach and understand.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.

Fuel pump

Fuel pump designed for easy starting.


Smart Start®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

- See-through fuel tank
- Tap 'n Go
- Detachable shaft

- Multi purpose
- Click on attachments

Specifications



Engine

Cylinder displacement	27.6 cm ³
Power output	0.85 kW
Maximum power speed	8000 rpm
Fuel tank volume	0.27 l
Fuel consumption	604 g/kWh
Idling speed	2800 rpm
Spark plug	NGK CMR6A
Electrode gap	0.5 mm
Clutch engagement speed (±120)	4200 rpm
Maximum rpm output shaft	7200 rpm
Exhaust emissions (CO2 EU V)	1580 g/kWh [1]



Transmission

Gear ratio	19
Drive gear angle	30 °



Capacity

Cutting width	43 cm
---------------	-------



Dimensions

Weight (excl. cutting equipment)	4.67 kg
Tube length	1257.41 mm
Tube diameter	25.4 mm



Equipment

OEM Grass blade	--
OEM Harness	Single harness
OEM Saw blade	--
OEM Trimmer head	T25 (L)



Lubricant

Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
----------------	---



Sound and Noise

Sound pressure level at operators ear	95 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)

[1] This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine.