

## Лента ремонтна, едностранно залепваща армирана



Описание на продукта: Едностранно лепяща лента tesa®, За широко приложение като фиксиране, уплътнение, маркиране и опаковане, дори върху грапави повърхности. Устойчива е на температури до 95°C, водо отблъскваща с добра адхезивна сила, гъстотата на мрежата е 27 нишки на кв. инч., много лесна за развиване, къса се с ръка.

### Приложение

За широко приложение като фиксиране, уплътнение, маркиране и опаковане, дори върху грапави повърхности

### Характеристики на продукта

- Устойчива на температури до 95 °C
- Добра адхезивна сила
- Водо отблъскваща
- Гъстота на мрежата: 27 нишки на кв. инч
- Много лесна за развиване
- Къса се с ръце

### Описание:

48 мм/50 м, сива, 27 нишки 95°C

### Technical Data

• Backing material	PE laminated cloth	• Elongation at break	18 %
• Total thickness	180 µm	• Tensile strength	30 N/cm
• Type of adhesive	natural rubber	• Temperature resistance (30 min)	95 °C
• Adhesion to steel	4.3 N/cm	• Mesh	27 count per square inch

### Properties

• Hand tearability	●●●	• Abrasion resistance	●
• Straight tear edges	●●	• Water resistance	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low