Технически характеристики

Лента ремонтна, едностранно залепваща армирана

Описание на продукта: Едностранно лепяща лента tesa®, За широко приложение като фиксиране, уплътнение, маркиране и опаковане, дори върху грапави повърхности. Устойчива е на температури до 950С, водо отблъскваща с добра адхезивна сила, гъстотата на мрежата е 27 нишки на кв. инч., много лесна за развиване, къса се с ръка.

Приложение

За широко приложение като фиксиране, уплътнение, маркиране и опаковане, дори върху грапави повърхности

Характеристики на продукта

– Устойчива на температури до 95 °C
– Добра адрхезивна сила
– Водо отблъскваща
– Гъстота на мрежата: 27 нишки на кв. инч
– Много лесна за развиване
– Къса се с ръце

Описание:

48 мм/50 м, черна, 27 нишки 95°C

Ташев- Галвинг ООД
www.tashev-galving.com

Technical Data

Backing material	PE laminated cloth	Elongation at break	18 %
Total thickness	180 µm	Tensile strength	30 N/cm
Type of adhesive	natural rubber	Temperature resistance (30 min)	95 °C
Adhesion to steel	4.3 N/cm	Mesh	27 count per square inch

Properties

Hand tearability	●●●	Abrasion resistance	●
Straight tear edges	●●	Water resistance	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low