



PRODUCT INFORMATION

EUROCEL 700 RDA

Short description:

Double sided adhesive tape

Product Data

Backing:	0.028 mm transparent BOPP film
Adhesive:	synthetic rubber
Liner:	double sided brown siliconized paper
Total thickness (without liner)	0.098 mm
Adhesion to steel	o.s. 20 N/25mm c.s. 30 N/25mm
Tensile strength MD	100 N/25mm
Elongation at break	140 %
Temp. Resistance	60 °C

Application

Double sided tape suitable for fixing of photographs, pattern books and other light samples and easy jobs.
Easy to use.

Features	Benefits
Synthetic rubber adhesive	<ul style="list-style-type: none"> ➤ High tack and high adhesion level both sides ➤ Good adhesion on different surfaces
Bopp film backing	<ul style="list-style-type: none"> ➤ High elongation ➤ Hand tearable*

**Feature available for few articles only*

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss