

FB/SD, snap-type ridge conductor holder; for fixing of conductors on roof ridges



item code	material	clp. r/r [mm]	L [mm]	ps [pcs]	ref.
FB-SD160-170Cu	Cu	8	160-170	100	064 000
FB-SD160-170Niro	V2A	8	160-170	100	063 999
FB-SD180-260Cu	Cu	8	180-260	100	063 963
FB-SD180-260Niro	V2A	8	180-260	100	063 964

BS, concrete base; for positioning of 8 mm round wires on flat roofs, frost resistant



item code	material	dn [mm]	weight [kg]	pieces	ref.
BS-recyclable	concrete	175 x 128 x 73	1	1	081 904
BS-concrete	K/concrete		1	1	063 934

UL, cleat; for 8 mm round wires



item code	material	spec.	clp. r/r [mm]	ps [pcs]	ref.
UL8-10/28fv	fv	hole spacing 28 mm	8-10	500	006 209
UL8-10/28Cu	Cu	hole spacing 28 mm	8-10	500	006 564
UL16/38fv	fv	hole spacing 38 mm	16	500	006 211

VS/UL, twist protection cleat; for 8 mm round wires



item code	material	clp. r/r [mm]	ps [pcs]	ref.
VS/ULNiro	V2A	6-8	100	063 872
VS/ULCu	Cu	6-8	100	063 871

DDF, roof bushing; for sealing of roofs at down conductor lead-in, for tiled and corrugated sheet roofs (drilling hole Ø 16 mm)



item code	material	spec.	for Ø [mm]	ps [pcs]	ref.
DDF/K8-10	K	Ø 34 mm, bore hole 16 mm	8-10	25	064 821