


## Цилиндър Festo за пневматични задвижки двойнодействащ ф 32x160 мм, 0.6-12 bar, G 1/8", DSBC-32-160-PPVA-N3



| Feature                                  | Value  |
|--|--|
| Stroke                                   | 160 mm   |
| Piston diameter                          | 32 mm  |
| Piston rod thread                        | M10x1.25   |
| Type code                                | DSBC   |
| Cushioning                               | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                        | Any  |
| Conforms to standard                     | ISO 15552  |
| Piston rod end                           | External thread  |
| Design                                   | Piston<br>Piston rod<br>Profile barrel                             |
| Position sensing                         | For proximity sensor   |
| Symbol                                   | 00991235   |
| Variants                                 | Piston rod at one end  |
| Operating pressure                       | 0.06 MPa ... 1.2 MPa   |
| Operating pressure                       | 0.6 bar ... 12 bar   |
| Mode of operation                        | Double-acting  |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| Ambient temperature                      | -20 °C ... 80 °C   |
| Impact energy in the end positions       | 0.4 J  |
| Cushioning length                        | 17 mm  |
| Theoretical force at 6 bar, retracting   | 415 N  |
| Theoretical force at 6 bar, advancing    | 483 N  |
| Moving mass at 0 mm stroke               | 110 g  |
| Additional weight per 10 mm stroke       | 27 g   |
| Basic weight with 0 mm stroke            | 465 g  |
| Additional moving mass per 10 mm stroke  | 9 g  |
| Type of mounting                         | Optionally:<br>With internal thread<br>With accessories            |
| Pneumatic connection                     | G1/8   |
| Note on materials                        | RoHS-compliant   |
| Cover material                           | Die-cast aluminum, coated  |
| Piston seal material                     | TPE-U(PU)  |
| Material of piston                       | Wrought aluminum alloy   |

| Feature                        | Value                                   |
|--------------------------------|---|
| Piston rod material            | High-alloy steel                        |
| Piston rod wiper seal material | TPE-U(PU)                               |
| Buffer seal material           | TPE-U(PU)                               |
| Cushion piston material        | POM                                     |
| Material of cylinder barrel    | Wrought aluminum alloy, smooth-anodized |
| Nut material                   | Steel, galvanized                       |
| Material of bearing            | POM                                     |
| Flange screws material         | Steel, galvanized                       |

Ташев-Галвинг ООД  
[www.tashev-galving.com](http://www.tashev-galving.com)

Продукт: [Цилиндър Festo за пневматични задвижки двойнодействащ ф 32x160 мм, 0.6-12 bar, G 1/8", DSBC-32-160-PPVA-N3](#)

Категория: [Пневматични задвижвания](#)

Марка: [Festo](#)

Тип: [Цилиндър Festo](#)