

800/1 Z Bits



Anwendung: Schlitzschrauben

Antrieb: $\frac{1}{4}$ "-Sechskant, passend für Halter nach
DIN ISO 1173-D 6,3

Ausführung: Zähhart, für den universellen Einsatz

	 mm	 mm	 mm	 mm	 mm
05056200001	0,5	3,0	25	1"	3,0
05056005001	0,5	3,0	39	1 $\frac{17}{32}$ "	3,0
05072050001	0,5	4,0	25	1"	4,0
05056007001	0,5	4,0	39	1 $\frac{17}{32}$ "	4,0
05056010001	0,6	3,5	39	1 $\frac{17}{32}$ "	3,5
05072055001	0,6	4,5	25	1"	4,5
05056015001	0,6	4,5	39	1 $\frac{17}{32}$ "	4,5
05072057001	0,8	5,5	25	1"	5,5
05056020001	0,8	4,0	39	1 $\frac{17}{32}$ "	4,0
05056025001	0,8	5,5	39	1 $\frac{17}{32}$ "	5,5
05072059001	1,0	5,5	25	1"	5,5
05056030001	1,0	5,5	39	1 $\frac{17}{32}$ "	5,5
05072061001	1,2	6,5	25	1"	6,2
05072063001	1,2	8,0	25	1"	8,0
05056037001	1,2	6,5	39	1 $\frac{17}{32}$ "	6,5
05056040001	1,2	8,0	39	1 $\frac{17}{32}$ "	8,0
05072065001	1,6	8,0	25	1"	8,0
05056045001	1,6	8,0	39	1 $\frac{17}{32}$ "	8,0