Demolition tools DCR 100

DCR 100 is our lightest crusher designed for our DXR 140 demolition robot to ensure high working efficiency. Despite its low weight it is possible to demolish a 400 mm thick wall. The crusher ensures great performance in a variety of applications such as demolition of concrete and brick constructions, staircases, roofs as well as sensitive locations inside buildings.

Jaw opening, 25 mm

min

● Jaw opening, 425 mm

max

Crushing 34 t

force

Cutting force 94 t

Article number: CONCRETE CRUSHER DCR 100 Standard - 966 78 63-01



1 от 2 4.6.2019, 15:12 ч.

SPECIFICATIONS

Hydraulics Specifications Hydraulic oil flow 55 I/min Cutting force 94 t Crushing force 34 t 360° Rotation angle 200 bar Incoming pressure, max 200 bar Operating pressure Max

Dimensions

| | Operating pressure Max |
|---------------------|------------------------|
| Dimensions | |
| Jaw depth | 185 mm |
| Jaw opening, min | 25 mm |
| Jaw opening, max | 425 mm |
| Rebar size, max | 28 mm |
| Product size length | 1000 mm |
| Product size width | 730 mm |
| Product size height | 330 mm |
| Weight | 192 kg |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | 2.0 0 |
| | |
| | ϕ_{i} |
| | |
| | NO. |
| | |
| | 10.2 |
| | 7 4 |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

2 от 2 4.6.2019, 15:12 ч.