


PRODUCT CATALOGUE

Outdoor Power Equipment and Accessories

HITACHI

Inspire the Next¹



2 Hitachi
YEAR
PETROL TOOL
WARRANTY

Terms & conditions apply

2015

2 Hitachi YEAR PETROL TOOL WARRANTY*

Terms & conditions apply. Online registration required

Now more than ever, you need tools you can rely on.

Hitachi Power Tools offer an extended warranty on all outdoor power equipment when registered within 4 weeks of purchase.

Simply visit www.hitachi-powertools.co.uk/opewarranty.html and complete the registration form supplied.

What does the extended warranty cover?

We undertake to replace or repair any part found to be defective in material or workmanship, within 24 months (15 months for Hire Fleets) of delivery to the original purchaser.

What is not covered?

Defects arising from neglect, misuse or accident, except as provided by statute. Accessories and other consumable items are also excluded from this Guarantee.

How do I get my tool repaired?

Contact your nearest Hitachi authorised service agent. You can find this on our website or by calling us on 01908 660663. You will need to provide your proof of purchase and warranty registration number to the service agent.

I have purchased a cordless outdoor power tool. Is this covered under the warranty?

Li-Ion cordless tools are covered by a separate extended warranty. Please see www.hitachi-powertools.co.uk for details.



Scan this barcode
to register your
petrol tool

www.hitachi-powertools.co.uk/service



36V Li-Ion Cordless

BL36200 RB36DL/L4
CG36DL/L5 CG36DAL/L4
CH36DL CS36DL




Grasstrimmers/Brushcutters

CG22EAP2/WJ CG22EAP2/WA
CG24EA2/WN CG27EA2/WN



Smart-Fit Brushcutters

CG27EBDP/LP
CG22EAP2/WE



Brushcutters

CG40EJ(T) CG47EJ(T)



Hedgetrimmers

CH22EAP2/WA CH22EBP2/WC
CH22ECP2/WC CH22ECP2/WE
CH27EAP/LW



Chainsaws

CS33EDT/LA CS33EB/L2
CS40EA/WF CS51EAP/WJ
CS27EPA(S)



Blowers

RB24E/LA RB24EAP/JS
RB100EF



Augers

DA300E DA200E(SP)



Accessories

Chains & Bars Auger Bits
Lubricants Canisters



PPE

Footwear Clothing
Headgear Safety Glasses



HITACHI KOKI'S GROWTH STRATEGY

The Hitachi Koki Group is aiming for a major expansion of its outdoor power equipment so they can become the driving force behind future strategic growth. The Group will realize steady growth by using its advanced technical capabilities to focus on developing original new products not being produced by other companies, accelerating global development, and actively expanding sales in newly emerging markets where growth potential is high.




GROWTH OF OUTDOOR POWER EQUIPMENT

Outdoor power equipment, which has large markets and is comparatively unaffected by economic volatility, will undergo a force behind future strategic growth. The framework for bolstering production capacity in China is finally in place and the product lineup is being assembled. In the future, the Group will further strengthen its products so they are price competitive and conform with secondary exhaust emission regulations in Europe and the US, and aggressively expand its sales channels globally.



E-ALD (ENGINE-ANALYSIS LEADING DESIGN) AND QUALITY CONTROL

By using a leading-edge technology via computer analysis called E-ALD (Engine-Analysis Leading Design), the Group is developing outdoor power equipment designed to take maximum advantage of engine performance. It also has a stringent quality control program, and its products are without exception subject to rigid inspections and tests at each stage of processing. Parts are scrutinized for flaws by expert inspectors. Components are thoroughly tested at assembly lines to ensure optimum performance, and each finished product is carefully examined to assure Hitachi's standard quality.



PUREFIRE

Introducing a new generation of two-stroke engines

Hitachi's innovative 'PureFire' two-stroke engine produces ultra-low emissions without the need for special or additional internal moving parts. During the intake / compression stroke, the optimised scavenging system within the cylinder and crankcase walls, significantly increase the atomization of the fuel/air mixture which results in a much more efficient combustion process. Then, in the combustion/exhaust stroke, the exhaust exits through a small catalytic converter in the muffler where the remaining hydrocarbons turn into carbon dioxide.



PureFire Engine

The world first certified to the stringent California Air Resources Board (CARB) Tier 3 emission regulations.

Official Emission Regulations		Certification Levels	
	CARB Tier 3	24cc	40cc
HC + NOx	50	38	47
CO	805	235	224

HC+NOx : Hydrocarbon Plus Oxides of Nitrogen

CO: Carbon Monoxide

S-START SYSTEM


Up to 50% less pulling force required

S-start is ideal for those who like to have soft and smooth engine starting. It is suitable for professional users too, who can save time and energy from reduced effort.

QUICK TWIST HANDLE

Five position adjustable handle

A 180° Angle adjustable pivoting handle with 5 positions makes vertical cuts and shaping easier than ever. Suitable for left or right handed use.



LI-ION CORDLESS OUTDOOR POWER TOOLS


Light Weight

Hitachi Li-Ion batteries are 40% lighter than Ni-MH batteries, allowing longer use and greater control.




Long Service Life

Unique protection circuitry in Hitachi Li-Ion batteries prevents overload, overcharge and high discharge, giving them up to 300% longer service life than similar batteries.



Environmentally Friendly

Hitachi Li-Ion batteries contain no harmful Cadmium, making them better for the environment. Also, Hitachi Li-Ion batteries have an extremely low self-discharge rate. If a battery is not used, the battery charge will drop by only 5% in 40 days, meaning that less energy is needed to recharge it. Finally, Hitachi Li-Ion batteries have no memory effect, making it possible to top up the battery charge at any time.



Hitachi Li-Ion batteries hold their charge for longer, which means there is no discernible loss of performance throughout the battery charge.

The user should be aware that the machine may cut out when the battery needs recharging. This is not a battery fault; the new technology protects the battery cell, giving extended charging cycles when compared to previous battery technology.

When the battery is recharged, the machine will operate normally.

New Batteries

Electric discharge may be low from new batteries or batteries that have not been used for a long period of time. This is a temporary phenomenon; normal operation will be achieved after charging and discharging the batteries two or three times.

How to make your Hitachi Li-Ion batteries last longer...

Always recharge your batteries before they become completely exhausted.

When you feel the tool losing power, stop using the tool and recharge the battery. If you continue to use the battery until it is completely drained, this may damage it and shorten its life.

Avoid recharging at high temperatures.

A rechargeable battery will be hot immediately after use. If you recharge it while it is hot, the internal chemical composition can be damaged, shortening the battery life. Let the battery cool for a while before recharging.

750Wh


36V **Li-ION**
BATTERY

Charge Overnight,
Work All Day. ¹



3 **HITACHI**
YEAR
ELECTRIC POWER TOOL
WARRANTY

¹Terms & conditions apply



¹ "Work All Day" means BL36200 Back Pack Power Supply provides approx. 8 hours of runtime for the model CH36DL when on a full charge. ² "ZERO Emission" means this product series operates with no exhaust emissions. ³ "EASY Maintenance" means there is no need to drain fuel for storage, clean an air filter, etc.

High Capacity

To Provide Longer Runtime

BL36200

36V Back Pack Power Supply*1
.....

Up to
10

Times Longer
Runtime
per Charge*2

Approx. 800
Recharge Cycles*3



Remote Switch Panel

makes it easy to check the remaining battery power even when the tool is in use



Compatible with
Hitachi 36V Lithium-ion
cordless tools



Carrier Handle

Multiplex
Protection Circuit

Low Power
Consumption

USB
Output Terminal



Flexible Power Cord
can be routed right or left
for ease of use



Padded Backpack
Style Carrier
ergonomic padded design
for greater comfort

36V

750Wh*4

5.9kg

(without adapter and carrier)

BSL3620

36V Slide Lithium-ion Battery*1



36V

2.0Ah*4

BSL3626

36V Slide Lithium-ion Battery*1



36V

2.6Ah*4

36V Lithium-ion
Cordless Series



3 HITACHI
YEAR
ELECTRIC POWER TOOL
WARRANTY

*Terms & conditions apply.



3 HITACHI
YEAR
ELECTRIC POWER TOOL
WARRANTY

*Terms & conditions apply.



3 HITACHI
YEAR
ELECTRIC POWER TOOL
WARRANTY

*Terms & conditions apply.



3 HITACHI
YEAR
ELECTRIC POWER TOOL
WARRANTY

*Terms & conditions apply.

*1 Sold separately.

*2 A comparison between the model CS36DL (BL36200) and the same model CS36DL (BSL3620). The runtime per charge may vary according to operating conditions.

*3 With charger UC36VRS. The recharging cycles during a product lifetime may vary according to discharging conditions.

*4 The figures of battery energy/capacity are nominal values.

NEW

ZERO Emission | LOW Noise | EASY Maintenance

Compact Top Handle Design*11 for more control

- **CS36DL/LL**
- Cordless Chain Saw

*11 Top handle chainsaws are for use by trained arborists only

300mm Guide Bar**LED Light****3.6kg**

(without battery)

Cutting Performance per Charge*7

BSL3620

BL36200

Approx.
140
cutsApprox.
1,400
cuts

Test Conditions:
Cut 50mm×50mm cedar timber.

*7 The amount of cut may vary according to operating conditions.



Triple-Edged Blade for fine cut

- **CH36DL/LL**
- Cordless Hedge Trimmer

620mm Blade**4-Stage Speed****3.2kg**

(without battery)


Runtime per Charge*8

BSL3620


BL36200

Approx.
50
min.Approx.
8
hr.

At the highest speed



Triple-Edged Blade



Low Noise, Low Vibration and High-Efficiency Disc Motor

- **CG36DL/CG36DAL**
- Cordless Grass Trimmers

Cutting Dia. 310mm**Telescopic Pipe*9****4.7 - 5.2kg**

(without battery)

Runtime per Charge*8

BSL3620

BL36200

Approx.
35min.
(Normal)
15min.
(High)Approx.
5.5hr.
(Normal)
2.5hr.
(High)

Types of Handle and Pipe

Model	Handle	Pipe
CG36DL	Bike	Single
CG36DAL	Loop	Telescopic



High-Efficiency and Durable Brushless Motor to deliver large air volume*10

- **RB36DL**
- Cordless Blower

Air Volume 800m³/h**4-Mode+Turbo Mode****3.0kg**

(without battery)


Runtime per Charge*8

BSL3620

BL36200

Approx.
8
min.Approx.
80
min.

In mode 4



*10 In comparison with Hitachi's conventional DC brushed motor.

*5 "ZERO Emission" means this product series operates with no exhaust emissions. *6 "EASY Maintenance" means there is no need to drain fuel for storage, clean an air filter, etc. *8 The runtime per charge may vary according to operating conditions.

BL36200

Back Pack Power Supply

- Compatible with Hitachi 36V Lithium-Ion cordless tools
- 10 times longer runtime per charge¹
- Remote switch panel makes it easy to check the remaining battery power even when the tool is in use

Battery: Type	Lithium-Ion
Voltage	36V
Capacity	21Ah ² (750Wh)
Output Terminal	USB (A Type)
Dimensions (L x W x H)	109 x 250 x 330mm
Weight: Power Supply	5.9kg
Adapter	0.5kg
Carrier	1.0kg



*ONLINE REGISTRATION REQUIRED WITHIN 28 DAYS OF PURCHASE

¹ Compared to BSL3620.
The runtime per charge may vary according to operating conditions

Standard equipment:
Carrier, charger(UC36YRSL), Adapter with cover, arm band, knob bolts, M5 screws

CS36DL

Cordless Top Handle Chainsaw

Compact Top Handle Design¹ for more control
Oil Tank with Backlight to easily check the remaining chain oil
Toolless Chain Adjuster
Chain-oil Flow Adjuster
Convenient Retractable Hook

Battery Voltage	36V
Guide Bar Length	300mm
Chain Speed	8.3m/s
Type of Guide Bar	Sprocket nose
Chain Pitch	9.52mm (3/8")
Overall Length	618mm
Weight (without battery)	3.6kg



CS36DL/LL
1 x 2.0Ah Li-Ion battery
UC36YRSL fan cooled charger
Chain oil, bar cover, round file

CS36DL/L4
Body only
Chain oil, bar cover, round file

PLEASE NOTE: ALL TOP HANDLE SAWS ARE FOR USE BY TRAINED ARBORISTS ONLY



*ONLINE REGISTRATION REQUIRED WITHIN 28 DAYS OF PURCHASE

CH36DL

Cordless Hedgetrimmer

Triple edged blade for cleaner cutting
4 stage speed selection
Slim grip handle
Wide sub handle
Durable aluminium bottom cover

Battery Voltage	36V
Blade: Length	620mm
Effective	550mm
No Load Speed (stroke)	1000 - 1500/min
Blade Pitch	35mm
Overall Length	1104mm
Weight (without battery)	3.2kg

CH36DL/LL
1 x 2.0Ah Li-Ion battery
UC36YRSL fan cooled charger
Blade cover

CH36DL/L4
Body only
Blade cover



*ONLINE REGISTRATION REQUIRED WITHIN 28 DAYS OF PURCHASE

Standard equipment:
Blade cover

CG36DL/L5
Cordless Grass Trimmer - Body Only

- High efficiency disc motor with low noise and vibration
- Variable speed dial
- Electronic brake

Battery Voltage	36V
Cutting Capacity Dia.	310mm
No Load Speed	5800-7000/min
Overall Length:	1900mm
Weight (without battery)	4.9kg



*ONLINE REGISTRATION
REQUIRED WITHIN
28 DAYS OF PURCHASE

Standard equipment:
Nylon head, shoulder belt, safety glasses, wrenches

CG36DAL/L4
Cordless Grass trimmer - Body Only

- High efficiency disc motor with low noise and vibration
- Variable speed dial
- Electronic brake
- Telescopic pipe for compact transportation
- Easy to release lock lever

Battery Voltage	36V
Cutting Capacity Dia.	310mm
No Load Speed	5800-7000/min
Overall Length:	
Extended	1880mm
With Shaft Withdrawn	1320mm
Weight (without battery)	5.0kg



*ONLINE REGISTRATION
REQUIRED WITHIN
28 DAYS OF PURCHASE

Standard equipment:
Nylon head, shoulder belt, safety glasses, wrenches

RB36DL/L4
Cordless Blower - Body Only

- Durable, high efficiency brushless motor delivers large air volume
- 4 mode switch
- Turbo mode for extra power
- Balanced design

Battery Voltage	36V
Air Volume	680m ³ /h
Turbo Mode	800m ³ /h
Air Velocity	45m/s
Turbo Mode	53m/s
Overall Length	948mm
Weight (without battery)	3.0kg



*ONLINE REGISTRATION
REQUIRED WITHIN
28 DAYS OF PURCHASE

Standard equipment:
Nozzle



ТОВ «ГЕЛВІНГ ООД»
galving.com



Ташев-Галвинг ООД
www.tashev-galving.com

CG22EAP2/WJ

Loop Handle Grasstrimmer/Brushcutter



- Lightweight and compact
- Loop front handle
- Stand keeps cutter upright to protect tank
- New PureFire engine meets European Stage 2 standards for low emissions

Displacement	21.1cc
Max Power	0.63kW (0.84hp)
Cutting Diameter	470mm
Fuel Tank Capacity	450cc
Diameter of Pipe	24mm
Dry Weight	3.9kg



Standard equipment:
Bump feed, box wrench, hex wrench, spanner, safety glasses

CG22EAP2/WA

Loop Handle Brushcutter



- Lightweight and compact
- Loop front handle
- Stand keeps cutter upright to protect tank
- Solid steel drive shaft
- S start: soft and smooth engine recoil starter
- New PureFire engine meets European Stage 2 standards for low emissions

Displacement	21.1cc
Max Power	0.63kW (0.84hp)
Cutting Diameter	460mm
Fuel Tank Capacity	450cc
Diameter of Pipe	24mm
Dry Weight	4.4kg



Standard equipment:
Blade, bump feed, harness, box wrench, hex wrench, spanner, safety glasses

Optional Parts

Attachments for straight shaft single handle Brushcutters.

Suitable for models CG22EAS(SLP), CG27EJ(SLP), CG24EKS(SL)

CG-HTB

Hedgetrimmer Attachment

Blade length 550mm

Weight 1.5kg

EAN: 4934528739011

CG-PSB

Pole Saw Attachment

Guide bar length 250mm

Weight 1.2kg

EAN: 4934528723003

CG-MCB

Mini Cultivator Attachment

Weight 2.3kg

EAN: 4934528331383



Note: these parts are covered by the standard 12 month warranty

CG24EA2/WN
Loop Handle Brushcutter



- Lightweight and compact
- Loop front handle
- Solid steel drive shaft
- S start: soft and smooth engine recoil starter

Displacement	23.9cc
Max Power	0.85kW (1.1hp)
Fuel Tank Capacity	520cc
Diameter of Pipe	24mm
Dimensions	1765 x 410 x 335mm
Dry Weight	4.6kg



Standard equipment:
Blade, harness, bump feed, box wrench, hex wrench, spanner, safety glasses

CG27EA2/WN
Loop Handle Brushcutter



- Loop front handle
- Solid steel drive shaft
- S start: soft and smooth engine recoil starter

Displacement	26.9cc
Max Power	0.9kW (1.2hp)
Fuel Tank Capacity	520cc
Diameter of Pipe	24mm
Dimensions	1765 x 410 x 335mm
Dry Weight	4.9kg



Standard equipment:
Blade, harness, bump feed, box wrench, hex wrench, spanner, safety glasses

SOLID STEEL DRIVE SHAFT



A solid steel drive shaft offers greater durability and long service life.

Note: Smart-Fit brushcutters are fitted with square section driveshafts.

Not fitted to bent shaft brushcutter CG22EAB(LP)



CG27EBDP/WA
Smart-Fit Loop Handle Brushcutter



- Loop front handle
- Nylon trimmer head as standard
- Accepts a range of attachments including hedgetrimmer, pole saw, edger and mini cultivator
- Easy to remove attachments allow for compact transporting
- New PureFire engine meets European standards for low emissions
- High durability engine with 2 piece piston ring
- Ignition control system
- Low vibration level
- Low noise
- Spindle lock system

Displacement	26.9cc
Max Power	0.9kW (1.2hp)
Fuel Tank Capacity	520cc
Diameter of Pipe	24mm
Dimensions	1782 x 320 x 253mm
Dry Weight	5.3kg



Standard equipment:
 Bump feed, box wrench, hex wrench, safety glasses, harness

CG22EAP2/WE
Smart-Fit Loop Handle Brushcutter



- S start: soft and smooth engine recoil starter
- New PureFire engine meets European Stage 2 standards for low emissions
- Loop front handle
- Nylon trimmer head as standard
- Detachable front end allows use of optional attachments
- Solid steel square section drive shaft

Displacement	21.1cc
Max Power	0.63kW (0.84hp)
Fuel Tank Capacity	450cc
Diameter of Pipe	24mm
Dry Weight	4.7kg



Standard equipment:
 Bump feed, box wrench, hex wrench, safety glasses, harness

Smart-fit attachments extend the capabilities of the CG27EBDP(SL) and CG22EAP2(SL), and are simple to detach and transport. All Smart-Fit attachments are fitted with a square section drive shaft.



CG-MC
Mini Cultivator Attachment
For aerating and cultivating flower beds
Length 869mm
Weight 2.8kg
EAN: 4934528331390
Standard Equipment: Box wrench, wheel screw



CG-GT
Grass Trimmer Attachment
Also accepts a blade (not supplied)
Length 860mm
Weight 1.7kg
EAN: 4934528382323
Standard Equipment: Bump feed head



CG-HT
Hedgetrimmer Attachment
For long-reach hedge trimming
Length 1426mm
Weight 2.3kg
EAN: 4934528739028
Standard Equipment: Handle



CG-PE
Portable Edger Attachment
For edging along paths and flower beds
Length 835mm
Weight 2.3kg
EAN: 4934528373444
Standard Equipment: Box wrench, wheel screw



CG-PS
Pole Saw Attachment
For pruning trees and shrubs
Length 1179mm
Weight 1.7kg
EAN: 4934528723010
Standard Equipment: Box wrench



CG-EX
Extension Kit
For use with the CG-PS only
Length 900mm
Weight 0.9kg
EAN: 4934528723058



Note: these parts are covered by the standard 12 month warranty

CG40EJ(T)
Bike Handle Brushcutter



- Bike type front handles
- Left and right handles separately adjustable for greater control
- Handles swivel for easy storage and transportation
- Solid steel drive shaft

Displacement	39.8cc
Max Power	1.31kW (1.75hp)
Fuel Tank Capacity	1000cc
Diameter of Pipe	28mm
Dimensions	1790 x 665 x 580mm
Dry Weight	7.7kg
EAN (head)	49345280478705
EAN (shaft)	4934528378708



Standard equipment:
 3 point blade with cover, bump feed, box wrench, hex wrench, spanner, safety glasses, harness

CG47EJ(T)
Bike Handle Brushcutter



- Bike type front handles
- Left and right handles separately adjustable for greater control
- Handles swivel for easy storage and transportation
- Solid steel drive shaft

Displacement	46.5cc
Max Power	1.75kW (2.34hp)
Fuel Tank Capacity	1000cc
Diameter of Pipe	28mm
Dimensions	1805 x 665 x 580mm
Dry Weight	8.2kg
EAN (head)	4934528471775
EAN (shaft)	4934528371778



Standard equipment:
 3 point blade with cover, bump feed, box wrench, hex wrench, spanner, safety glasses, harness

Type	Name	Specification			Item No	Used On
		Dia.	Teeth	Thickness		
	Blade B4/9/1.6	9"	4	1.6mm	6695789	CG22EAD, CG22EAS, CG24EASP, CG24EKD, CG24EKS, CG25EUS, CG27EASP, CG28EJ, CG31EBS, CG33EJ
	Blade B4/10/1.6	10"	4	1.6mm	6695790	
	Blade B3/10/2.0	10"	3	2.0mm	6695791	CG27EASP, CG28EJ, CG31EBS, CG33EJ, CG40EAF, CG40EAS, CG40EF, CG40EJ, CG40EK, CG40EY, CG40EYA, CG47EF, CG47EJ, CG47EY
	Blade B3/12/3.0	12"	3	3.0mm	6695792	
	Blade B24/8/1.6	8"	24	1.6	6695793	CG40EJ, CG40EK, CG40EY, CG40EYA, CG47EJ, CG47EY
	Nylon Head CH-100 (W/Nylon Line)	No line feed system			6695785	CG22EAB, CG22EAD, CG22EAS, CG24EASP, CG24EKB, CG24EKD, CG24EKS, CG25EUS, CG27EASP, CG28EJ, CG31EBS, CG33EJ
	Nylon Head CH-100	No line feed system			6695786	
	Nylon Head CH-300 (W/Cutter Holder Cap)	Manual line feed system			6695787	CG27EASP, CG28EJ, CG31EBS, CG33EJ, CG40EAF, CG40EAS, CG40EBF, CG40EJ, CG40EK, CG40EY, CG40EYA, CG47EF, CG47EJ, CG47EY
	Nylon Head CH-300	Manual line feed system			6695788	
	Nylon Head TH-97RBY	R M8 x 1.25 Nut			6695776	Former model CG22EJ(SLB)
	Nylon Head TH-97M	L M10 x 1.25 Nut			6695777	Former model CG22EJ(SL)
	Nylon Head TH-97U2	L M10 x 1.25 Nut L M8 x 1.25 Nut			6695778	CG28EJ, CG33EJ
	Nylon Head TH-97L	L M8 x 1.25 Bolt			6695779	-
	Nylon Head TH-97LU	L M10 x 1.25 Nut L M8 x 1.25 Nut			6695780	CG40EJ, CG40EK, CG40EY, CG40EYA, CG47EJ, CG47EY, CG40EF, CG47EF
	Nylon Head TH-97LM	L M10 x 1.25 Nut			6695781	
	Nylon Head BF-4	M8 x 1.25 Nut			6695782	CG22EAB, CG24EKB
	Nylon Head Z-5	M8 x 1.25 Nut			6695783	CG22EAD, CG22EASP, CG24EKD, CG24EKS
	Nylon Head BF-5	M10 x 1.25 Nut M8 x 1.25 Nut			6695784	CG22EAD, CG22EAS, CG24EASP, CG24EKD, CG24EKS, CG25EUS, CG27EAS, CG27EASP, CG28EJ, CG31EBS, CG33EJ

Note: these parts are covered by the standard 12 month warranty

Nylon Lines for Grass Trimmers/Brushcutters

Hitachi high quality co-polyamide lines are made for agricultural and gardening applications and are known as the best in the market. The material is strong and tough with high abrasion resistance and can be used on thick tough vegetation with weeds and brambles. The special blend of raw material overcomes two of the most common difficulties encountered with intensive line use, namely line breakage at the eyelet of the nylon head and line fusing in the head. Thanks to the aerodynamic shape of the helicoidal lines, they have outstanding air penetration resulting in a significant noise reduction. Depending on the size of the line and the rotation of the machine, the noise level reduction may go up to about 15%. The lines have lower vibration, improving the lifetime of the trimmer machine and improving efficiency because the machine will reach its optimal speed faster.




Hitachi nylon lines are colour coded to allow easy distinction between sizes:

Green: 2.0mm

Orange: 2.4mm

Red: 2.65mm

Yellow: 3.0mm

	Size	Length	Weight (g)	Colour	Part Number	EAN
Round Line						
	2.00	15	54	Green	781001	8717574018899
	2.00	63	226	Green	781002	8717574018905
	2.00	126	453	Green	781003	8717574018912
	2.40	15	77	Orange	781004	8717574018929
	2.40	44	226	Orange	781005	8717574018936
	2.40	88	453	Orange	781006	8717574018943
	2.65	15	94	Red	781007	8717574018950
	2.65	36	226	Red	781008	8717574018967
	2.65	72	453	Red	781009	8717574018974
	3.00	15	121	Yellow	781010	8717574018981
	3.00	28	226	Yellow	781011	8717574018998
	3.00	56	453	Yellow	781012	8717574019001
Square Line						
	2.00	15	68	Green	781021	8717574019018
	2.00	50	226	Green	781022	8717574019025
	2.00	99	453	Green	781023	8717574019032
	2.40	15	98	Orange	781024	8717574019049
	2.40	34	226	Orange	781025	8717574019056
	2.40	69	453	Orange	781026	8717574019063
	2.65	15	120	Red	781027	8717574019070
	2.65	28	226	Red	781028	8717574019087
	2.65	56	453	Red	781029	8717574019094
	3.00	15	154	Yellow	781030	8717574019101
	3.00	22	226	Yellow	781031	8717574019117
	3.00	44	453	Yellow	781032	8717574019124
Helicoidal Line						
	2.00	15	50	Green	781041	8717574019131
	2.00	63	185	Green	781042	8717574019148
	2.00	126	370	Green	781043	8717574019155
	2.40	15	65	Orange	781044	8717574019162
	2.40	44	185	Orange	781045	8717574019179
	2.40	88	370	Orange	781046	8717574019186
	2.65	15	75	Red	781047	8717574019193
	2.65	36	185	Red	781048	8717574019209
	2.65	72	370	Red	781049	8717574019216
	3.00	15	96	Yellow	781050	8717574019223
	3.00	28	185	Yellow	781051	8717574019230
	3.00	56	370	Yellow	781052	8717574019247

Note: these parts are covered by the standard 12 month warranty

HEDGETRIMMERS



The Quick-Twist angle-adjustable handle uses a simple lock-on/lock-off button to set the handle at 0°, 45° and 90° left and right. This allows for easy vertical trimming, suitable for both left- and right-handed users.



Push the lock button to change the angle of the twist handle. This is only possible when the throttle lever is released.

Wide space designed between operator's hands and hedges



When blades are moving, the lock button can not be pushed. The operator must release the throttle lever before pushing the locking button to change the handle position.

CH22EAP2/WA

Double Sided Hedgetrimmer

- New PureFire engine meets European standards for low emissions
- Wide angle adjustable handle can be easily locked in 5 positions for ease of use
- S start: soft and smooth engine recoil starter

Displacement	21.1cc
Max Power	0.65kW (0.87hp)
Fuel Tank Capacity	300cc
Cutter: Length	500mm
Effective	444mm
Cutter Pitch	30mm
Cutter Speed	0.91m/sec
At Rated Speed	10000/min
Blade Type	Double sided
Dimensions	936 x 238 x 236mm
Dry Weight	4.3kg
EAN	4966376222537



Standard equipment:
Box wrench, hex wrench, blade cover

CH22EBP2/WC

Double Sided Hedgetrimmer

- New blade with 3 cutting edges
- New PureFire engine meets European standards for low emissions
- Wide angle adjustable handle can be easily locked in 5 positions for ease of use
- S start: soft and smooth engine recoil starter

Displacement	21.1cc
Max Power	0.65kW (0.87hp)
Fuel Tank Capacity	300cc
Cutter: Length	620mm
Effective	554mm
Cutter Pitch	35mm
Cutter Speed	1.06m/sec
At Rated Speed	10000/min
Blade Type	Double sided
Dimensions	1053 x 238 x 219mm
Dry Weight	4.7kg
EAN	4966376222728



Standard equipment:
Box wrench, hex wrench, blade cover



CH22ECP2/WC
Double Sided Hedgetrimmer

- Low vibration design - less than one third the vibration of standard model
- New blade with 3 cutting edges
- New PureFire engine meets European standards for low emissions
- Wide angle adjustable handle can be easily locked in 5 positions for ease of use
- S start: soft and smooth engine recoil starter

Displacement	21.1cc
Max Power	0.65kW (0.87hp)
Fuel Tank Capacity	300cc
Cutter: Length	620mm
Effective	554mm
Cutter Pitch	35mm
Cutter Speed	1.06m/sec
At Rated Speed	10000/min
Blade Type	Double sided
Dimensions	1053 x 250 x 197mm
Dry Weight	5.0kg
EAN	4966376222926



Standard equipment:
 Box wrench, hex wrench, blade cover

CH22ECP2/WE
Double Sided Hedgetrimmer


- **Low vibration design - less than one third the vibration of standard model**
- New blade with 3 cutting edges
- New PureFire engine meets European standards for low emissions
- Wide angle adjustable handle can be easily locked in 5 positions for ease of use
- S start: soft and smooth engine recoil starter

Displacement	21.1cc
Max Power	0.65kW (0.87hp)
Fuel Tank Capacity	300cc
Cutter: Length	780mm
Effective	694mm
Cutter Pitch	35mm
Cutter Speed	1.06m/sec
At Rated Speed	10000/min
Blade Type	Double sided
Dimensions	1207 x 250 x 197mm
Dry Weight	5.0kg
EAN	4966376222933



Standard equipment:
 Box wrench, hex wrench, blade cover

Pole hedgetrimmers can function as both a brushcutter and a hedgetrimmer. The head angle is easily adjustable by a lever at the gear case to suit cutting and trimming applications either on the ground or high above.



CH27EPA/LW Pole Hedgetrimmer



- For trimming medium height and high hedges
- Head angle is adjustable from 90° down to 45° up
- S start: soft and smooth engine recoil starter
- Overall length 2.3m

Displacement	26.9cc
Max Power	0.88kW (1.23hp)
Fuel Tank Capacity	520cc
Cutter: Length	550mm
Cutter Speed	0.95m/sec
At Rated Speed	7500/min
Blade Type	Double Sided
Dimensions	2300 x 240 x 250mm
Dry Weight	6.2Kg
Barcode	4934528838844




Standard equipment:
Box wrench, hex wrench, blade cover, harness

CS-EX
Extension Kit - Optional Accessory

Length: 600mm
Weight: 0.6kg

CHAINSAWS



Hitachi top handle chainsaws are lightweight and compact, designed for tree servicing and working in confined spaces. A well balanced design and single lever control give greater usability.

Side access chain tensioner:
Allows saw chain to be adjusted through the side case



Chain oil supply adjustment:
Located on the top for easy use



Thumb rest:
Easy to hold the unit stably & firmly



Screw to adjust engine speed:
Located on the top for easy use



Auto choke return system



Well balanced:
Rear eyelet for attaching rope



**PLEASE NOTE: TOP HANDLE
SAWS ARE FOR USE BY
TRAINED ARBORISTS ONLY**



PLEASE NOTE: ALL TOP HANDLE
SAWS ARE FOR USE BY
TRAINED ARBORISTS ONLY



CS33EDT/LA
Top Handle Chainsaw

- Lightweight & compact design
- Ideal for pruning
- Spring type anti-vibration system

Displacement	32.2cc
Max Power	1.3kW (1.74hp)
Fuel Tank Capacity	290cc
Chain Oil Tank Capacity	180cc
Chain Pitch	3/8"
Guide Bar Length	300mm
Type of Guide Bar Sprocket Nose	
Chain Gauge	1.27mm (0.05")
Dimensions	277 x 255 x 220mm
Dry Weight (exc. bar & chain)	3.4kg
EAN	4966376194025



Standard equipment: Chain, chain bar, bar cover, box wrench

CS33EB/WE
Standard Handle Chainsaw

- Compact & lightweight design
- New PureFire engine meets European Stage 2 standards for low emissions
- Priming bulb
- Auto-return choke

Displacement	32.2cc
Max Power	1.25kW (1.67hp)
Fuel Tank Capacity	350cc
Chain Oil Tank Capacity	250cc
Chain Pitch	3/8"
Guide Bar Length	350mm
Type of Guide Bar Double Guard®	
Chain Gauge	1.27mm (0.05")
Dimensions	389 x 226 x 280mm
Dry Weight (exc. bar & chain)	3.8kg
EAN	4966376177950
Double Guard is a registered trademark of Blount Inc.	



Standard equipment: Chain, chain bar, bar cover, box wrench



Ташев-Галвинг СООП
www.tashev-galving.com

HITACHI



Ташев-Галвинг ООУ
www.tashemgaling.com

CS40EA/WF
Standard Handle Chainsaw



- New PureFire engine meets European Stage 2 standards for low emissions
- Light weight, high power design
- Low vibration design
- S-Start Soft and smooth engine recoil starter
- Auto return choke
- Primer for easier starting

Displacement	39.6cc
Max Power	1.8kW (2.4hp)
Fuel Tank Capacity	380cc
Chain Oil Tank Capacity	240cc
Chain Pitch	8.26mm (0.325")
Guide Bar Length	380mm
Type of Guide Bar	Sprocket Nose
Chain Gauge	1.27mm (0.05")
Height	283mm
Width	229mm
Dry Weight (exc. bar & chain)	4.4kg
EAN	4966376182671



Standard equipment: Chain, chain bar, spike, bar cover, box wrench

CS51EAP/WJ
Standard Handle Chainsaw



- Built in decompressor for easy starting
- New PureFire engine meets European Stage 2 standards for low emissions
- Primer pump
- Auto return choke
- Spring type anti-vibration system

Displacement	50.1cc
Max Power	2.5kW (3.35hp)
Decompression System	Yes
Fuel Tank Capacity	530cc
Chain Oil Tank Capacity	270cc
Chain Pitch	8.26mm (0.325")
Guide Bar Length	500mm
Type of Guide Bar	Sprocket Nose
Chain Gauge	1.27mm (0.05")
Dimensions	391 x 232 x 294mm
Dry Weight (exc. bar & chain)	5.2kg
EAN	4966376194957



Built-in Decompressor

Easy start with less force required

Standard equipment: Chain, chain bar, bar cover, box wrench, screwdriver

CS27EPAP/LA
Pole Saw



- S start: soft and smooth engine recoil starter
- Overall length 2.4m

Displacement	26.9cc
Max Power	0.88kW (1.18hp)
Fuel Tank Capacity	520cc
Chain Oil Tank Capacity	160cc
Chain Pitch	9.5mm (3/8")
Guide Bar Length	250mm
Type of Guide Bar	Sprocket Nose
Chain Gauge	1.1mm (0.043")
Pole Diameter	24mm
Pole Length	1800m
Dimensions	2400 x 240 x 250mm
Dry Weight	5.6kg
EAN	4934528823307

Standard equipment:
Box wrench, hex wrench, spanner, harness



Ташев-Галвинг ООД
www.tashev-galving.com

CS-EX
Extension Kit - Optional Accessory

Length: 600mm
Weight: 0.6kg
EAN: 4934528723034

CS-EXB
Extension Kit - Optional Accessory

Length: 900mm
Weight: 0.9kg
EAN: 49 34528 723041

Note: the CS-EX/EXB are covered by the standard 12 month warranty



BLOWERS



RB24E/LA
Hand Held Blower


- New PureFire engine meets European Stage 2 standards for low emissions
- Soft grip handle
- Lightweight design suitable for professional or home use
- Throttle control lever
- Can be used as a vacuum with the optional vacuum kit

Displacement	23.9cc
Max Power	0.84kW (1.13hp)
Fuel Tank Capacity	600cc
Air Volume	10.3m ³ /min
Air Velocity	48.6m/sec
Dimensions (ex pipe)	365 x 269 x 360mm
Dry Weight	4.6kg
EAN	4934528418756



Standard equipment: Box wrench

RB-HVA
Vacuum Kit

- Converts RB24E blower into a vacuum
- Large capacity bag with shoulder strap

Bag Capacity	53 litres
Mulching Ratio	12:1
EAN	4934528318223



Note: these parts are covered by the standard 12 month warranty

RB24EAP/JS
Hand Held Blower


- Lightweight & compact design
- Hand held blower for home or professional use
- New PureFire engine meets European Stage 2 standards for low emissions

Displacement	23.9cc
Max Power	0.89kW (1.13hp)
Fuel Tank Capacity	520cc
Air Flow	12m ³ /min
Dimensions (ex pipe)	354 x 205 x 335
Dry Weight	3.9kg
EAN	4966376191529



AUGERS



DA300E Two Man Auger



- Suitable for auger bits up to 200mm diameter
- Two person operation
- Adjustable handles for easy storage
- Dual throttles for safer operation
- Auger bit not included

Displacement	50.2cc
Max Power	1.54kW (2.06hp)
Fuel Tank Capacity	1000cc
Shaft Diameter	25.4mm
Dimensions	1200 x 600 x 490mm
Dry Weight	17.0kg
EAN	4934528422555



DA200E(SP) One Man Auger



- Suitable for auger bits up to 200mm diameter
- Single person operation
- S start: soft and smooth engine recoil starter
- New PureFire engine meets European Stage 2 standards for low emissions
- Auger bit not included

Displacement	32.2cc
Max Power	1.15kW (1.34hp)
Fuel Tank Capacity	680cc
Shaft Diameter	25mm
Maximum Bit Size	200mm
Dimensions	452 x 300 x 430mm
Dry Weight	8.5kg
EAN	4934528818020




ACCESSORIES




Ташев-Галринг ООД
www.tashev-galring.com

All Hitachi saw chains are fabricated from special alloy steel. This specially engineered steel adds toughness and abrasion resistance. All Hitachi saw chain cutters are plated with hard industrial chrome. This process yields superior edge-holding qualities to other types of plating.

In the field, Hitachi saw chains stay sharp longer. Unlike the competition, every Hitachi saw chain is sharpened after assembly to cut fast out of the box. To reduce bearing wear during 'break in', all Hitachi chains are injected at the rivet bearing with a hypoid lubricant.


HITACHI SAW CHAINS							
	Length	Pitch	Gauge	No. of Links	Item Number	EAN	
	25cm (10")	3/8" LP	1.3mm (0.050")	40	781120	8717574021301	
	30cm (12")	3/8" LP	1.3mm (0.050")	45	781122	8717574021318	
	35cm (14")	3/8" LP	1.3mm (0.050")	52	781124	8717574021325	
	40cm (16")	3/8" LP	1.3mm (0.050")	57	781126	8717574021332	
	33cm (13")	0.325" Nk	1.3mm (0.050")	56	781133	8717574021349	
	38cm (15")	0.325" Nk	1.3mm (0.050")	64	781135	8717574021356	
	40cm (16")	0.325" Nk	1.3mm (0.050")	66	781136	8717574021363	
	45cm (18")	0.325" Nk	1.3mm (0.050")	72	781138	8717574021370	
	30.5m/100ft	3/8" LP	1.3mm (0.050")	1632	781192	8717574021455	
30.5m/100ft	0.325" Nk	1.3mm (0.050")	1848	781193	8717574021462		
LP: Low Profile Nk: Narrow kerf							

Hitachi chains are also available as a chain bar and the suitable chain packed into one package. All Hitachi chain bars are equipped with a sprocket nose.


HITACHI SAW CHAIN & BAR PACKAGES						
	Length	Pitch	Gauge	No. of Links	Item Number	EAN
	30cm (12")	3/8" LP	1.3mm (0.050")	45	781232	8717574021387
	35cm (14")	3/8" LP	1.3mm (0.050")	52	781234	8717574021394
	33cm (13")	0.325" Nk	1.3mm (0.050")	56	781243	8717574021417
	38cm (15")	0.325" Nk	1.3mm (0.050")	64	781245	8717574021424
	40cm (16")	0.325" Nk	1.3mm (0.050")	66	781246	8717574021431
	45cm (18")	0.325" Nk	1.3mm (0.050")	72	781248	8717574021448
LP: Low Profile Nk: Narrow kerf						

Note: these parts are covered by the standard 12 month warranty

HITACHI AUGER BITS

	Diameter	Total length	Spiral length	Arbor	Suitable For	Item Number	EAN
	55mm	1.1m	660mm	25.4mm	DA200E(SP) DA300E	714001	8717574017892
	80mm	1.1m	660mm	25.4mm		714002	8717574017908
	100mm	1.1m	660mm	25.4mm		714003	8717574017915
	120mm	1.1m	660mm	25.4mm		714004	8717574017922
	150mm	1.1m	660mm	25.4mm		714005	8717574017939
	200mm	1.1m	660mm	25.4mm		714006	8717574017946
	250mm	1.1m	660mm	25.4mm		714007	8717574017953
	300mm	1.1m	660mm	25.4mm		714008	8717574017960


HITACHI AUGER BIT EXTENSION

	Diameter	Total length	Suitable For	Item Number	EAN
	45mm	600mm	DA200E(SP) DA300E	714026	8717574018097


HITACHI AUGER BIT PINS (PAIR)

	Diameter	Total length	Spiral length	Item Number	EAN
	8mm	52mm	45mm	714025	8717574018080

HITACHI AUGER BIT REPLACEMENT KNIVES


	Suitable for auger bit	Item Number	EAN	Suitable for auger bit	Item Number	EAN
	55/80mm	714012	8717574017984	200mm	714016	8717574018028
	100mm	714013	8717574017991	250mm	714017	8717574018035
	120mm	714014	8717574018004	300mm	714018	8717574018042
	150mm	714015	8717574018011	All knives are supplied with spare bolts and nuts.		

HITACHI AUGER BIT REPLACEMENT POINTS


	Suitable for auger bit	Item Number	EAN	Suitable for auger bit	Item Number	EAN
	55mm	714021	8717574018059	200-300mm	714023	8717574018073
	80-150mm	714022	8717574018066			

Note: these parts are covered by the standard 12 month warranty

SEMI-SYNTHETIC LUBRICANT

	Description	Contents	Item Number	EAN
	Semi-synthetic lubricant specifically designed for excellent engine protection and performance in 2-stroke motorcycle engines. It guarantees superior control against exhaust system blocking and minimizes exhaust smoke.	100 ml	714811	8717574017854
		1 litre	714812	8717574017861

BIODEGRADABLE LUBRICANT

	Description	Contents	Item Number	EAN
	Biodegradable Chainsaw oil, specially formulated to satisfy the demanding requirements of a chainsaw. Besides lubricating the chain, Bio-Chainsaw oil also prevents the chain from overheating and loss of strength.	1 litre	714816	8717574017878
		5 litre	714817	8717574017885



Oil Display case




Special cap on 1 Litre can to prevent spillage




Note: these parts are covered by the standard 12 month warranty



CANISTERS

	Description	Item Number	EAN
	<ul style="list-style-type: none"> • Petrol canister made of HDPE • UN/BAM and TÜV approved • Including standard spout 	714821	8717574019377

CANISTERS

	Description	Item Number	EAN
	<ul style="list-style-type: none"> • Professional double canister for petrol and chainsaw oil made of HDPE • Volume of chambers: 5 and 3 l • UN/BAM and TÜV approved • Including standard spout 	714822	8717574019384

FILLING SYSTEM

	Description	Item Number	EAN
Prevents spillages and overfilling when refuelling			
	For fuel	714826	8717574019391
	For oil	714827	8717574019407

Note: these parts are covered by the standard 12 month warranty

PERSONAL PROTECTIVE EQUIPMENT (PPE)







HITACHI RUBBER CHAINSAW BOOTS

Material:	Natural rubber
Size range:	4 - 14 (European 37 - 50)
Standard:	EN ISO 20345 .SB.E / EN ISO 17249:2004 Class 2 (≥ 24 m/s)
Properties:	Chainsaw protection, protective toecap
Resistance:	Oils, fats, various chemicals



Hitachi chainsaw boots bear this mark to indicate their compliance with European safety standards.


Hitachi chainsaw boots conform to EN20345.

CLASS 2

HITACHI RUBBER CHAINSAW BOOTS

	Size (UK)	Size (EUR)	Item Number	EAN
	4	37	713537	8717574018615
	5	38	713538	8717574018639
	6	39	713539	8717574018653
	-	40	713540	8717574018677
	7	41	713541	8717574018691
	8	42	713542	8717574018714
	9	43	713543	8717574018738
	10	44	713544	8717574018752
	-	45	713545	8717574018776
	11	46	713546	8717574018790
	12	47	713547	8717574018813
	13	48	713548	8717574018837
	14	49	713549	8717574018851
	-	50	713550	8717574018875

Note: these parts are covered by the standard 12 month warranty





HITACHI LEATHER CHAINSAW BOOTS

Material:	Leather
Size range:	6 – 13 (European 39 – 48)
Standard:	EN ISO 17249:2004 EN 381 CLASS 1-2-3 Class 2 (\geq 24 m/s)
Properties:	Chainsaw protection, protective toecap
Resistance:	Oils, fats, various chemicals



CLASS 2

Hitachi chainsaw boots bear this mark to indicate their compliance with European safety standards.

Hitachi chainsaw boots conform to EN20345.

HITACHI LEATHER CHAINSAW BOOTS

	Size (UK)	Size (EUR)	Item Number	EAN
	6	39	714039	8717574019254
	6½	40	714040	8717574019261
	7	41	714041	8717574019278
	8	42	714042	8717574019285
	9	43	714043	8717574019292
	10	44	714044	8717574019308
	10½	45	714045	8717574019315
	11	46	714046	8717574019322
	12	47	714047	8717574019339
	13	48	714048	8717574019346

Note: these parts are covered by the standard 12 month warranty



HITACHI HEAD PROTECTION**HELMET**

Standard:	EN 397
Material	ABS
Inner Fitting:	4 point, 180° swivel

VISOR

Standard	EN 1731
Material	Matt finished steel
Mesh Size	1.8mm x 1.8mm
Light Reduction	0.35

EAR PROTECTION

Standard	EN 352-3
Noise Reduction	SNR 27

HEAD PROTECTION			
	Description	Item Number	EAN
	Forestry combination headgear with: Full helmet Metal visor Ear defenders UV indicator	713511	8717574025842
	Landscaping combination headgear with: Metal visor Ear defenders	713512	8717574025859

Note: these parts are covered by the standard 12 month warranty

Hitachi chainsaw and forestry clothing provides the optimal balance between protection and comfort, while being light, comfortable and easy to maintain.


Hitachi's well-equipped testing laboratory offers the possibility to find solutions according to the specific needs of chainsaw users. Professional end users are regularly called upon to test Hitachi chainsaw and forestry clothing in practice, paying great attention to ergonomics, quality, durability and comfort.

The results of all these tests are incorporated into the clothing so that the optimal balance is achieved between protection, security and comfort.


Hitachi chainsaw clothing is made of a beaver nylon, comprising 49% cotton and 51% polyester nylon so the outside of the clothing is very durable, water resistant and dirt repelling. The inside is soft and comfortable to wear.

Of course, all models meet the current European standards, because your safety is our priority. The various levels of protection are indicated on the clothing by an icon with the standard EN 381 accompanied by the class.

Size	Length	Height	Chest size	Waist size
S	46 - 48cm (18-19")	164 - 182cm (64-72")	88 - 96cm (35-38")	76 - 84cm (30-33")
M	50 - 52cm (20-21")	164 - 182cm (64-72")	96 - 104cm (38-41")	84 - 92cm (33-36")
L	54 - 56cm (21-22")	170 - 188cm (67-74")	104 - 112cm (41-44")	92 - 100cm (36-39")
XL	58 - 60cm (23-24")	170 - 188cm (67-74")	112 - 120cm (44-47")	100 - 108cm (39-43")
XXL	62 - 64cm (24-25")	176 - 194cm (70-76")	120 - 128cm (47-50")	108 - 116cm (43-47")
XXXL	66 - 68 (26-27)	176 - 194cm (70-76")	128 - 139cm (50-55")	116 - 124cm (47-49")



Front View



Rear View




Protected Area

B

C

A



All Hitachi chainsaw clothing is washable up to 60 degrees but is not suitable for tumble drying.




All Hitachi chainsaw trousers are equipped with type A protection. They are suitable for professional foresters who are trained to work in forestry at ground level.

Type A offers 180° protection in front of each leg plus 5 cm on the inside of the right leg and 5cm on the outside of the left leg. The protection begins no more than 5cm from the bottom of the leg and stops at least 20cm above the crotch.

Hitachi forestry jackets are available as a standard model for general use or chainsaw protective model with Type A protection



HITACHI CHAINSAW JACKETS	
Protection:	Type A
Standard:	EN 381-11 Class 0 (up to 16 m/s)
Size range:	S - 3XL
Layers:	9
Colour	Pine green/ fluorescent orange

HITACHI FORESTRY JACKETS			
Protective Jacket (Type A)	SIZE	Item Number	EAN
 CLASS 0 	S	713632	8717574022315
	M	713633	8717574022322
	L	713634	8717574022339
	XL	713635	8717574022346
	2XL	713636	8717574022353
	3XL	713637	8717574022360
Jacket Without Protection	SIZE	Item Number	EAN
	S	713642	8717574022377
	M	713643	8717574022384
	L	713644	8717574022391
	XL	713645	8717574022407
	2XL	713646	8717574022414
	3XL	713647	8717574022421

Note: these parts are covered by the standard 12 month warranty

LUMBAR COVERING

BUTTONS FOR BRACES

SLIT POCKETS

TRIPLE STITCHED CROTCH FOR REINFORCEMENT

WATERPROOF OUTER



BELT LOOPS

LOCKABLE BACK POCKET WITH FLAP

RULER POCKET WITH FLAP



CLASS 1

HITACHI FORESTRY TROUSERS	
Protection:	Type A
Standard:	EN 381-5 Class 1 (up to 20 m/s)
Size range:	S - 3XL
Layers:	9
Colour	Pine green/ fluorescent orange

LUMBAR COVERING

ZIP FOR EASY ACCESS

LOCKABLE BACK POCKET WITH FLAP

SLIT POCKETS

TRIPLE STITCHED CROTCH FOR REINFORCEMENT

WATERPROOF OUTER



ADJUSTABLE BRACES

FRONT POCKET


ELASTIC LUMBAR BAND

RULER POCKET WITH FLAP









CLASS 1

HITACHI FORESTRY BIB & BRACE	
Protection:	Type A
Standard:	EN 381-5 EN 340:2003 Class 1 (up to 20 m/s)
Size range:	S - 3XL
Layers:	9
Colour	Pine green/ fluorescent orange



CLASS 1

HITACHI FORESTRY LEGGINGS	
Protection:	Type A
Standard:	EN 381-5 Class 1 (up to 20 m/s)
Size range:	One size
Layers:	9
Colour	Pine green/ fluorescent orange


HITACHI FORESTRY LEG PROTECTION				
Forestry Trousers - Type A		SIZE	Item Number	EAN
 CLASS 1 	S	713602	8717574022186	
	M	713603	8717574022193	
	L	713604	8717574022209	
	XL	713605	8717574022216	
	2XL	713606	8717574022223	
	3XL	713607	8717574022230	
	Forestry Bib & Brace - Type A		SIZE	Item Number
 CLASS 1 	S	713612	8717574022247	
	M	713613	8717574022254	
	L	713614	8717574022261	
	XL	713615	8717574022278	
	2XL	713616	8717574022285	
	3XL	713617	8717574022292	
	Forestry Leggings		SIZE	Item Number
 CLASS 1 	One size	713621	8717574022308	


Note: these parts are covered by the standard 12 month warranty

SAFETY GLASSES

	Description	Lens	Item Number	EAN
	Flexible big vision goggle Both sides anti fogging Fits over most prescription glasses Comply with EN166	Clear	750403	8717472818621
	Comfortable cover spectacle Fits over most prescription glasses Flexible temples for pressure free fit Large ventilated side shields Temple length adjustable Both sides anti fogging Comply with EN166	Clear	713501	8717574017793
	Safety glasses with modern design Individual temple inclination Individual temple length adjustment Indirect ventilation Easy lens replacement Outside of lens hard coated for extreme scratch resistance Inside of lens anti fogging Comply with EN166	Clear	713502	8717574017809
		Grey	713503	8717574017816
		Amber	713504	8717574017823
	Set of safety glasses with modern design In robust spectacle case. Glasses with grey lens and additional interchangeable clear lens	1 x Grey 1 x Clear	713505	8717574017830
	Full vision goggle Exceptional wearing comfort Complete side protection Fits over most prescription glasses Outstanding ventilation Outside of lens hard coated for extreme scratch resistance Inside of lens anti fogging Comply with EN166	Clear	713506	8717574017847

Note: these parts are covered by the standard 12 month warranty

HEARING PROTECTION			
	Description	Item Number	EAN
	5 Pairs of ear plugs (10 pcs) SNR 28 Comply with EN 352	750404	8717472819208

BREATHING PROTECTION			
	Description	Item Number	EAN
	Fine Dust mask With valve FFP3 Comply with EN 149	750407	8717574000436



Note: these parts are covered by the standard 12 month warranty

TOOLS

BL36200.....	10
CG22EAP2/WJ.....	14
CG22EAP2/WA.....	14
CG24EA2/WN.....	15
CG27EA2/WN.....	15
CG27EBDP/LP.....	17
CG22EAP2/WE.....	17
CG36DAL/L4.....	11
CG36DL/L5.....	11
CG40EJ(T).....	19
CG47EJ(T).....	19
CG-EX.....	18
CG-GT.....	18
CG-HT.....	18
CG-HTB.....	14
CG-MC.....	18
CG-MCB.....	14
CG-PE.....	18
CG-PS.....	18
CG-PSB.....	14
CH22EAP2/WA.....	24
CH22EBP2/WC.....	24
CH22ECP2/WC.....	25
CH22ECP2/WE.....	25
CH27EAP/LW.....	26
CH36DL/L4.....	10
CH36DL/LL.....	10
CS27EPA(S).....	33
CS33EB/L2.....	29
CS33EDT/LA.....	29
CS36DL/L4.....	10
CS36DL/LL.....	10
CS40EA/WF.....	32
CS51EAP/WJ.....	32
CS-EX.....	35
CS-EXB.....	35
DA200E(SP).....	37
DA300E.....	37
RB-HVA.....	35
RB24E/LA.....	35
RB24EAP/JS.....	35
RB36DL/L4.....	11

ACCESSORIES

Auger Bits.....	40
Auger Bit Extension.....	40
Auger Bit Pins.....	40
Auger Bit Knives.....	40
Auger Bit Points.....	40
Brushcutter Blades.....	20
Canisters.....	42
Filling System.....	42
Line Feeds.....	20
Lubricants.....	41
Nylon Lines.....	21
Saw Chains & Bars.....	39

PPE

Chainsaw Boots:	
Rubber.....	44
Leather.....	46
Protective Headgear.....	48
Protective Jackets.....	55
Protective Trousers.....	52
Dust Mask.....	55
Earplugs.....	55
Glasses.....	54

2 Hitachi YEAR PETROL TOOL WARRANTY*

Terms & conditions apply. Online registration required

Now more than ever, you need tools you can rely on.

Hitachi Power Tools offer an extended warranty on all outdoor power equipment when registered within 4 weeks of purchase.

Simply visit www.hitachi-powertools.co.uk/opewarranty.html and complete the registration form supplied.

What does the extended warranty cover?

We undertake to replace or repair any part found to be defective in material or workmanship, within 24 months (15 months for Hire Fleets) of delivery to the original purchaser.

What is not covered?

Defects arising from neglect, misuse or accident, except as provided by statute. Accessories and other consumable items are also excluded from this Guarantee.

How do I get my tool repaired?

Contact your nearest Hitachi authorised service agent. You can find this on our website or by calling us on 01908 660663. You will need to provide your proof of purchase and warranty registration number to the service agent.

I have purchased a cordless outdoor power tool. Is this covered under the warranty?

Li-Ion cordless tools are covered by a separate extended warranty. Please see www.hitachi-powertools.co.uk for details.



Scan this barcode
to register your
petrol tool

www.hitachi-powertools.co.uk/service

HITACHI

Inspire the Next

Hitachi Power Tools (UK) Ltd

Precedent Drive, Rooksley, Milton Keynes,
Buckinghamshire MK13 8PJ

Sales Enquiries

Telephone: 01908 354700
Fax: 01908 232868
Email: sales@hitachi-powertools.
co.uk

General Enquiries

Telephone: 01908 660663
Fax: 01908 606642
Email: info@hitachi-powertools.
co.uk

Internet:
co.uk

www.hitachi-powertools.com

www.low-vibration.com

A member of



European Power Tool Association



Your local dealer is: