

D26204K



Router Combination

- Full wave electronic speed control with feedback ensures the selected speed is maintained under any load for a consistent finish in all grades of timber, aluminium and plastics
- Variable speed control 16,000 to 27,000 which enables the router bit to be optimised for application
- Compact, light weight design that increase ease of use and user comfort

Features

- Full wave electronic speed control with feedback ensures the selected speed is maintained under any load for a consistent finish in all grades of timber, aluminium and plastics
- Variable speed control 16,000 to 27,000 which enables the router bit to be optimised for application
- Compact, light weight design that increase ease of use and user comfort
- Aluminium motor housing can be transitioned quickly to a fixed base attachment increasing the versatility of the machine
- Plunge base incorporates fine tune rod for precise depth adjustment
- Five position adjustable turret enables stepped or repeated plunge cuts
- Over moulded rubber handles provide a comfortable and secure grip
- Dual LED lights increase the visibility around the router bit during operation
- Multiple spindle lock detants enables quick and simple router bit change

Standard

- 2 x Parallel fences
- 2 x Dust extraction adapter
- 8 mm collet (¼" GB)

- 17 mm spanner
- Plunge and Fixed base
- Centering cone
- Tough Kit Box

Specifications

Power Input	900 Watts
Power Output	620 Watts
No Load Speed	16000-27000 rpm
Plunge Stroke/Movement	55 mm
Collet Size	6-8 mm
Max. Cutter Diameter	36 mm
Hmotnost	2.9 kg
Length	110 mm
Height	270 mm
Hand/Arm Vibration	7.0 m/s ²
Uncertainty K 1 (Vibration)	2.7 m/s ²
Sound Pressure	77 dB(A)
Uncertainty K 1 (Sound)	3.0 dB(A)
Accoustic Pressure	88 dB(A)
Uncertainty K 2 (Sound)	3.0 dB(A)

Ташев-Галвинг ООД
www.tashev-galving.com