

Технически характеристики



WEEE Number: 80133970

INSTALLATION INSTRUCTION

LED WATERPROOF







TECHNICAL DATA:

MODEL	WATTS	LUMENS	CRI	PF	BEAM ANGLE	DIMENSION	INPUT POWER	CLIPS TYPE	MAX CONNECTABLE UNITS
VT-60018	18W	2160LM	>80	>0.9	120°	600x72x78mm	AC: 200-240V, 50/60Hz	ABS CLIP	20 UNITS
VT-120036	36W	4320LM	>80	>0.9	120°	1200x72x78mm	AC: 200-240V, 50/60Hz	ABS CLIP	10 UNITS
VT-150048	48W	5760LM	>80	>0.9	120° 1	1500x72x78mm	AC: 200-240V, 50/60Hz	ABS CLIP	8 UNITS
VT-120136-T	36W	4320LM	>80	>0.9	120°	1200x72x78mm	AC: 200-240V, 50/60Hz	SS CLIP	10 UNITS
VT-150148-T	48W	5760LM	>80	>0.9	120°	1500x72x78mm	AC: 200-240V, 50/60Hz	SS CLIP	8 UNITS

INTRODUCTION & WARRANTY

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any another query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best. The warranty is valid for 3 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. The products are suitable for 10-12 Hours Daily operation. Usage of product for 24 Hours a day would void the warranty. This product is warranted for manufacturing defects only.

WARNING!

- 1. Please make sure to turn off the power before starting the installation.
- 2. The light source of this luminaire is not replaceable, when the light source reaches its end of life the whole luminaire should be replaced.
- 3. If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
- 4. Installation must be performed by a qualified electrician.



This marking indicates that this product should not be disposed of with other household wastes.



Caution, risk of electric shock.







TABLE 1

MODEL	L1
VT-60018	290+40mm
VT-120036	830+40mm
VT-150048	1090+40mm
VT-120136-T	830+40mm
VT-150148-T	1090+40mm