

Search term

Search

**STEINEL**  
For DIYers  
and home users

**STEINEL**<sup>®</sup>

## Sensor downlight RS PRO DL 100

**Professional integrator (without sensor).** Downlight RS PRO DL 100, ideal for large installations, e.g. WC facilities at airports, in schools, office buildings or administration centres, interconnectable by cable with RS PRO DL 100, recessed ceiling mounting, without sensor.


Version

Interconnectable  
by cableOptional  
remote control

RS PRO DL 100 downlight in the slave version (without sensor, without remote control). Can be seamlessly integrated into false ceilings. Features: two chip-controlled electronic ballasts for 2 x 18 W/TC-DEL.

### More uses

Large systems (e.g. WC facilities) at airports, in schools, office buildings or administration centres interconnectable by cable with RS PRO DL 100



Light distribution curves for RS PRO DL 100

### Technical specifications Sensor downlight RS PRO DL 100 without sensor

European Article Number (EAN)	4007841002633
Dimensions(w x h x d)	240 x 394 x 90 mm
	230 - 240 V, 50 Hz (can be operated on

<b>Voltage</b>	direct current in emergency lighting mode)
<b>Output</b>	2 x 18 W / TC-DEL (2 electronic ballasts)
<b>Additional switching capacity</b>	maximum of 4 further lights
<b>IP rating</b>	IP20
<b>Protection class</b>	II
<b>Temperature range</b>	-10-+50
<b>Model</b>	without sensor
<b>With lamp</b>	No



[Contacts](#)  
[STEINEL near you](#)  
[Find a sales partner](#)

[Help | FAQs](#)  
[Privacy Policy](#)  
[Imprint](#)  
[Sitemap](#)

Customer service until 8 p.m.:  
**+49 (0) 52 45 / 4 48-188**

©2013 STEINEL

**Newsletter**

Enter e-mail address

Submit

Follow us on: