



Search

**STEINEL**  
Home improvement  
and home

**STEINEL**

## Design **sensor** outdoor light L 20

**Ambient lighting in the square!** Design sensor outdoor light L 20, ideal for entrances and house fronts, 180 ° viewing angle range up to 10 m, time and twilight threshold, sensor tilts to 90 ° for exact alignment of the detection range, stainless steel trim.



max. 10 m

high quality  
stainless steel materialshockproof  
material IK07

### Live comfortably and at the same time saving energy.

Improved quality of life, safety and energy savings through intelligent sensor technology from STEINEL. **lights ON / OFF - automatically** Highly innovative sensors react to movement and light conditions, and turn on the light automatically after a programmable time off again. **eyecatcher in the square ! The sensor outdoor light L 20 captivates by its pure geometry.** And it has high quality, stainless steel bezel, and millions of good STEINEL sensor technology for ease of use, safety and energy efficiency at an attractive price. The detection angle is 180 ° with a range of up to 10 m. The sensor lens can be used for fine adjustment of the detection angle vertically pivoted by 90 °. For additional adjustment of the detection zone to the local conditions are in shrouds. Sensor and light cover are made of polycarbonate. Refined: the transparent on the back chassis a wonderful atmosphere light on the house wall where the light sensor is placed. The E27 socket accepts both conventional light bulbs with max. 60 W as well as energy-saving lamps and LED lamps with max. 20 W (not included). The setting of time and twilight threshold are easily accessible via dial on the bottom of the sensor. Thanks to an easy to mount the sensor space-L lamp is wired 20 simply and quickly.

### Other areas of application

ideal for building entrances and house fronts

### Specifications Design Outdoor light sensor L 20

|                               |                    |
|-------------------------------|--------------------|
| European Article Number (EAN) | 4007841566814      |
| Dimensions (H x W x D)        | 240 x 230 x 80 mm  |
| Mains connection              | 230 - 240 V, 50 Hz |

|   |                                   |
|---|-----------------------------------|
| Sensor Type   | Passive Infrared                  |
| Performance   | max. 60 W / E27                   |
| Angle of coverage                                     | 180 °                             |
| segmental acquisition suppression possible            | Yes                               |
| Range   | max. 10 m                         |
| Swivels vertically                                    | 90 °                              |
| Response brightness                                   | 2-2000 lx                         |
| Time setting  | 8 sec - 35 min                    |
| (IP)  | IP44                              |
| Protection class                                      | II                                |
| Dielectric strength                                   | IK07                              |
| Material  | Plastic with stainless steel trim |
| With bulbs  | No                                |
| Suitable for light bulbs, energy saving lamps and LED | Yes                               |

[Contact](#)  
STEINEL site  
Country and  
language

[Help | FAQ](#)  
[Privacy Policy](#)  
[Imprint](#)  
[Sitemap](#)

Customer to 20 clock:  
**+49 (0) 52 45/4 48-188**

© 2012 STEINEL

Newsletter

Follow us: