


Photo-cell-controlled light

LN 1 LED

EAN 4007841 649715



LED

long life LED
50.000 h



3000K
warm-white



IP54



5 - 200 lux



IK07



beam 2 m



energy saving



3 JAHRE
HERSTELLER
GARANTIE
steinel.de/garantie



CE



TÜV Nord GS

Function description

Slim and versatile. LED, naturally. STEINEL outdoor light LN 1 LED for permanently illuminating all sides of the building at night. 4,5 W STEINEL LED lighting system, 350 lm, light comes ON automatically at dusk, including adhesive house numbers, impact-resistant material (to IK 07).

Technical specifications

Dimensions (L x W x H)	56 x 300 x 195 mm	Capability of masking out individual segments	No
Mains power supply	230 – 240 V / 50 – 60 Hz	Electronic scalability	No
Sensor Technology	Light sensor	Mechanical scalability	No
Output	4,5 W	Photo-cell controller	Yes
Interconnection	No	Twilight setting	5 – 200 lx
Slave mode/selectable	No	Basic light level function	No
Luminous flux	350 lm	Soft light start	No
Colour temperature	3000 K	Impact resistance	IK07
Colour variation LED	SDCM3	IP-rating	IP54
Colour Rendering Index CRI	80-89	Protection class	II
With lamp	Yes, STEINEL LED system	Ambient temperature	-20 – 40 °C
Lamp	LED cannot be replaced	Housing material	Plastic
LED life expectancy (max. °C)	50000 h	Cover material	Plastic, opal
Drop in luminous flux in accordance with LM80	L70B10	Manufacturer's Warranty	3 years
Base	without	includes sheet of self-adhesive numbers	Yes
LED cooling system	Passive Thermo Control	Settings via	Potentiometers
With motion detector	No	PU1, EAN	4007841649715
Sneak-by guard	No		

Photo-cell-controlled light

LN 1 LED

EAN 4007841 649715



Dimension Drawing

