Sensor-switched LED floodlight

XLED slim

white

EAN 4007841 012069



30 years (Ø 4,5h / day) | 4000K neutral white | infrared sensor 160° | max. 8 m | IP44 | 2 - 1000 lux | 2 sec - 70 min | ideal 2 m | energy saving | manufacture's warranty steinel.de/garantie

Function description

Light meets elegance. Elegantly designed sensor LED floodlight XLED slim with 10,5 W, ideal for building entrances and pathways, pleasant and effective light (660 lm) requiring very little energy, sensor reach of up to 8 m, tilting range of +-30° (horizontal).

Technical specifications

Dimensions (L x W x H)	201 x 66 x 241 mm
Output	10,5 W
Interconnection	No
Luminous flux	660 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
With motion detector	Yes
Sneak-by guard	Yes

Time setting	2 s – 70 Min.
Main light adjustable	No
Settings via	Potentiometers
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	0,549 kg
Version	white
PU1, EAN	4007841012069

Ташев-Галвинг ООД
www.tashev-galving.com

Sensor-switched LED floodlight

XLED slim

white

EAN 4007841 012069

Detection Zone



Mögliche Montagehöhe: –
Orange: radial
Schwarz: tangential

Dimension Drawing



Ташев-Галвинг ООД
www.tashev-galving.com