

7440/41 Kraffform torque screwdriver set 0.3-3.0 Nm, 26 pieces

Series 7400 Kraffform Torque Screwdrivers



EAN:	4013288112354	Size:	255x210x62 mm
Part number:	05074738001	Weight:	802 g
Article number:	7440/41	Country of origin:	CZ
		Customs tariff number:	82079030

- Kraffform torque screwdriver set
- Suitable for bits with 1/4" hex head drive
- With Hex-Plus, TORX® and TORX PLUS® bits
- In a stable case
- High precision

Wera torque screwdriver set. Two torque screwdrivers with variable torque setting option with highest precision. Simple adjustment of the required torque value without any special tools. Easy-to-read scale value. Rapidaptor quick-release technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Kraffform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Includes bit assortment in a high quality and stable plastic case.

Set contents:



- 7400**
 05074700001 1 x art. no. 7440 x 0.3-1.2 Nm
 05074701001 1 x art. no. 7441 x 1.2-3.0 Nm



- 867/1 TZ TORX®**
 05066301001 1 x TX 6 x 25 mm
 05066302001 1 x TX 7 x 25 mm
 05066303001 1 x TX 8 x 25 mm
 05066304001 1 x TX 9 x 25 mm
 05066305001 1 x TX 10 x 25 mm
 05066308001 1 x TX 15 x 25 mm
 05066310001 1 x TX 20 x 25 mm
 05066312001 1 x TX 25 x 25 mm
 05066315001 1 x TX 30 x 25 mm



- 867/1 IP TORX PLUS®**
 05066274001 1 x 6 IP x 25 mm
 05066276001 1 x 7 IP x 25 mm
 05066278001 1 x 8 IP x 25 mm
 05066279001 1 x 9 IP x 25 mm
 05066280001 1 x 10 IP x 25 mm
 05066282001 1 x 15 IP x 25 mm
 05066284001 1 x 20 IP x 25 mm
 05066286001 1 x 25 IP x 25 mm
 05066288001 1 x 30 IP x 25 mm



- 840/1 Z Hex-Plus**
 05056305001 1 x 2 x 25 mm
 05056310001 1 x 2.5 x 25 mm
 05056315001 1 x 3 x 25 mm
 05056320001 1 x 4 x 25 mm
 05056325001 1 x 5 x 25 mm
 05056330001 1 x 6 x 25 mm

Adjustable Torque Screwdrivers



Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.

Simple setting



Simple setting of the required torque by hand.

Easy-to-read



Easy-to-read scale value.

Measurement accuracy



Measurement accuracy is $\pm 6\%$ (article 1430: $\pm 10\%$) in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Unlimited torque



Unlimited torque for loosening seized screws.

Versatile




Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.