

Технически характеристики

7440/41/42 Kraftform torque screwdriver set 0.3-6.0 Nm, 27 pieces

Series 7400 Kraftform Torque Screwdrivers













4013288113924 EAN:

05074739001 Part number:

7440/41/42 Article number:

Size:

255x210x62 mm

Weight: 1145 g

Country of origin: CZ

Customs tariff 82079030

number:















- Kraftform torque screwdriver set
- Suitable for bits with 1/4" hex head drive
- With Hex-Plus, TORX® and TORX PLUS® bits
- . In a stable case

Wera torque screwdriver set. Two high precision torque screwdrivers with variable torque settings. One torque screwdriver with Kraftform pistol handle for the transfer of especially high torque; multi-component for high working speeds and particularly ergonomic screwdriving. Simple adjustment of the required torque value without any special tools. Easy-to-read scale value. Rapidaptor quickrelease technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Includes a bit assortment in a high quality and stable plastic case.



<u>Технически характеристики</u>

Set contents:



7400

05074700001 1 x art. no. 7440 x 0.3-1.2 Nm 05074701001 1 x art. no. 7441 x 1.2-3.0 Nm



7400 Pistole

05074702001 1 x art. no. 7442 x 3.0-6.0 Nm



867/1 TZ TORX®

05066301001 1 x TX 6 x 25 mm 05066302001 1 x TX 7 x 25 mm 05066303001 1 x TX 8 x 25 mm 05066304001 1 x TX 9 x 25 mm 05066305001 1 x TX 10 x 25 mm 05066308001 1 x TX 15 x 25 mm 05066310001 1 x TX 20 x 25 mm 05066312001 1 x TX 25 x 25 mm 05066315001 1 x TX 30 x 25 mm



867/1 IP TORX PLUS®

05066274001 1 x 6 IP x 25 mm 05066276001 1 x 7 IP x 25 mm 05066278001 1 x 8 IP x 25 mm 05066279001 1 x 9 IP x 25 mm 05066280001 1 x 10 IP x 25 mm 05066282001 1 x 15 IP x 25 mm 05066284001 1 x 20 IP x 25 mm 05066286001 1 x 25 IP x 25 mm 05066288001 1 x 30 IP x 25 mm



840/1 Z Hex-Plus





Easy-to-read





Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.



Simple setting of the required torque by hand.



Easy-to-read scale value.

Measurement accuracy

Versatile

Rapid-in and self-lock

Rapid-out



Measurement accuracy is \pm 6 % (article 1430: \pm 10 %) in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.