

7443/61/9 Assembly set for tyre pressure control systems, 9 pieces

Series 7400 Krafftform Torque Screwdrivers - Variable torque adjustment models



EAN:	4013288168818	Size:	380x285x95 mm
Part number:	05074745001	Weight:	1109 g
Article number:	7443/61/9	Country of origin:	CZ
		Customs tariff number:	82054000

- Assembly set for tyre pressure control systems
- To monitor the tyre pressure on motor vehicles
- Optimum tyre pressure saves fuel and prevents tyre wear
- 9-piece set in a stable plastic case

9-piece tool set for the proper assembly and disassembly of tyre pressure control systems. Comes with torque technology for controlled screw tightening. Hand tool with multi-component Krafftform handle for high working speeds and ergonomic working. Two pre-set tools to connect the union nut with the screw and to fasten the sensor component to the valve. An adjustable Krafftform pistol handle for torque values of between 4.0 and 8.8 Nm. Two TX bits with holding function, socket adaptor, two sockets plus a valve dolly (for applications up to 4.5 Nm). Suitable for tyre control, systems from e.g. Schrader®, Alligator®, VDO®.



Set contents:



7400 pre-set, 105 mm
05074716001 1 x art. no. 7461 x 1.2 Nm x 1.2-3.0 Nm



7400 Pistolet
05074705001 1 x art. no. 7443 x 4.0-8.8 Nm



870/1
05136000001¹⁾ 1 x 1/4" x 25 mm
1) With friction ball; for manual nut spinner sockets



867/4 TORX® HF
05060082001 1 x TX 15 x 50 mm
05060083001 1 x TX 20 x 50 mm




327
05160111001 1 x 32 x 70 mm

Pre-set, adjustable Torque Screwdrivers



These tools are ideal for all applications where a constant, identical torque is required and where a high degree of repeat accuracy is needed. The torque value can be adjusted within the measuring range.

Adjustable Torque Screwdrivers



Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.

Simple setting



Simple setting of the required torque by hand.

Easy-to-read



Easy-to-read scale value.

Measurement accuracy




Measurement accuracy is $\pm 6\%$ (article 1430: $\pm 10\%$) in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Rapidaptor holder



Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool.

The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!