


160 i VDE-isolierter Schlitz-Schraubendreher



Anwendung: Schlitzschrauben

Klinge: Isoliert, stückgeprüft gemäß IEC 60900

Ausführung: Konische Schneide, Lasertip-Spitze

Griff: Kraftform mit Abrollschutz, mehrkomponentig

	 mm	 mm	 mm	 mm	 "	 "
05006100001 ¹⁾	0,4	2,5	80	81	$\frac{3}{32}$ "	3 $\frac{1}{8}$ "
05006105001 ¹⁾	0,5	3,0	100	81	$\frac{1}{8}$ "	4"
05006110001	0,6	3,5	100	81	$\frac{9}{64}$ "	4"
05006115001	0,8	4,0	100	98	$\frac{5}{32}$ "	4"
05006116001	0,8	4,0	150	98	$\frac{5}{32}$ "	6"
05006120001	1,0	5,5	125	98	$\frac{7}{32}$ "	5"
05006121001	1,0	5,5	200	98	$\frac{7}{32}$ "	8"
05006125001	1,2	6,5	150	105	$\frac{1}{4}$ "	6"
05006126001	1,2	6,5	200	105	$\frac{1}{4}$ "	8"
05006130001	1,2	8,0	175	112	$\frac{5}{16}$ "	7"
05006135001	1,6	8,0	200	112	$\frac{5}{16}$ "	8"
05006140001	1,6	10,0	200	112	$\frac{3}{8}$ "	8"

¹⁾ kein Lasertip