

- Einhell



Rotary Hammer TE-RH 950 5F Item No.: 4257978 Ident No.: 21011 Bar Code: 4006825663372

The Einhell rotary hammer TE-RH 950 5F combines five functions: Drilling or impact drilling, chiseling with & without lock, and screwdriving. The twospeed gearing allows screwdriving in the 1st gear and drilling in the 2nd gear. The pneumatic impact mechanism provides very good forward traction. There is a position switch for selecting all functions. There are large soft grip surfaces for a comfortable hold. For comfortable & user-friendly operation there is a continuous operation lock. The rotary hammer is equipped with a robust SDS-plus tool chuck, an infinitely adjustable drilling depth stop made of solid metal, and an additional drill chuck for screwdriving and drilling. Supplied in transport and storage case E-Box Basic.

Features & Benefits

- 5 functions: Drilling/impact drilling/chiseling with/without lock
- 2-speed gearing: High torque in 1st gear, high speed in 2nd gear
- One position switch for all functions
- Large soft grip surfaces on main handle
- Continuous operation lock: comfortable & user-friendly working
- Pneumatic impact mechanism for very good forward traction
- With rugged SDS-plus chuck with auto-slip-in function
- Speed electronics for material and application suitable working
- Infinitely adjustable drilling depth stop made of solid metal
- Additional drill chuck for screwdriving and drilling
- Supplied in transport and storage case E-Box Basic

Technical Data

- Mains supply
- Power
- Idle speed

- Impact power

- Tool holder

- Idle speed (gear 2)
- Impact rate
- 0-2600 min^-1 0-4500 min^-1 3 J SDS-plus

220-240 V | 50 Hz

950 W

28 mm

0-1200 min^-1

- Drilling capacity in concrete

Logistic Data

- Product weight	3.61 kg
- Gross weight single packaging	5.52 kg
- Dimensions single packaging	417 x 109 x 358 mm
- Pieces per export carton	4 Pieces
- Gross weight export carton	24.5 kg
- Dimensions export carton	385 x 486 x 440 mm
- Container quantity (20"/40"/40"HC)	1320 2760 3200









