

## UHE 2660-2 Quick (600697500) Multi Hammer

Plastic Carry Case; with Metabo Quick change chuck

Order no. 600697500 EAN 4007430306227



Product may differ from Image














- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for preselection of the speed and impact rate
- Two-speed gear unit: two drilling speeds for effective drilling in wood and metal
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Bottom switch protected against damage and dust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation
- Cable-protecting ball joint for optimal freedom of motion when working

www.metabo.com 1 / 2



| Technical data                      |                                |
|-------------------------------------|--------------------------------|
| Characteristics                     |                                |
| Max. single blow energy (EPTA)      | 2.8 J                          |
| Maximum impact rate                 | 4200 bpm                       |
| Rated input power                   | 800 W                          |
| Drill-Ø concrete with hammer drills | 26 mm / 1 1/32 "               |
| Drill-Ø masonry with core bits      | 68 mm / 2 11/16 "              |
| Drill Ø steel                       | 13 / 6 mm // 1/2 / 1/4 "       |
| Drill-Ø soft wood                   | 32 / 28 mm // 1 1/4 / 1 3/32 " |
| No-load speed                       | 0 - 1050 / 0 - 2500 rpm        |
| Revolutions at rated load           | 790 / 1860 rpm                 |
| Bit retainer                        | SDS-plus                       |
| Collar diameter                     | 50 mm / 1 31/32 "              |
| Weight (without power cable)        | 3.1 kg / 6.9 lbs               |
| Cable length                        | 4 m / 13 ft                    |
| Vibration                           |                                |
| Drilling in metal                   | 3.3 m/s <sup>2</sup>           |
| Uncertainty of measurement K        | 1.5 m/s²                       |
| Hammer drilling concrete            | 12.9 m/s²                      |
| Uncertainty of measurement K        | 2,4 m/s²                       |
| Chiseling                           | 8.5 m/s <sup>2</sup>           |
| Uncertainty of measurement K        | 1,5 m/s²                       |
| Noise emission                      |                                |
| Sound pressure level                | 88 dB(A)                       |
| Sound power level (LwA)             | 99 dB(A)                       |
| Uncertainty of measurement K        | ♦ 3 dB(A)                      |

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end

Drilling depth guide

Plastic carry case

Keyless chuck for tools with cylindrical shank

rubber-coated side handle

www.metabo.com 2 / 2