KHE 2444 (606154000) Combination Hammer

(220-240 V / 50 Hz); Plastic Carry Case

Order no. 606154000
EAN 4007430203748



Product may differ from Image



- Combination hammer for hammer drilling, drilling without impact and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

Ташев Галвинг ООД
www.tashev-galving.com

Technical data

Characteristics

Max. single blow energy (EPTA)	2.3 J
Maximum impact rate	5400 /min
Rated input power	800 W
Drill-Ø concrete with hammer drills	24 mm / 1 "
Drill-Ø masonry with core bits	68 mm / 2 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1230 /min
Revolutions at rated load	880 /min
Torque	15 Nm / 133 in-lbs
Bit retainer	SDS-plus
Collar diameter	43 mm / 1 11/16 "
Weight (without power cable)	2.4 kg / 5.3 lbs
Cable length	4 m / 13 ft m

Vibration

Hammer drilling concrete	13.7 m/s²
Uncertainty of measurement K	1.5 m/s²
Chiseling	15 m/s²
Uncertainty of measurement K	1.5 m/s²

Noise emission

Sound pressure level	87 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Hammer chuck for tools with SDS-plus shank end

Plastic carry case

Side handle

Drilling depth guide

Ташев-Галвинг ООД
www.tashev-galving.com