

Hot air tool - Professional Line

HM 2320 E

Case
EAN 4007841 089672
Article number 089672



series 5



Timer function

2300 W

2300 W Output

Display

Display (LCD)



80 - 650°C



stepless adjustable



150 - 500 l/Min.



Suitable for
pluggable nozzles



VDE



CE

Function description

Powerhouse of energy saving. Sustainable working for the professional tradesman or industry. The 2300 W HeatMatic 2320 E provides absolute safety even with sensitive materials thanks to the display and the precise temperature setting of 80-650°C.

Technical specifications

Temperature	80 – 650 °C
Airflow rate	150 – 500 l/min
Temperature setting	in 10°C steps by joystick
Settings made via	joystick
Temperature display	LCD display
Airflow control	Settings
Programming function	Yes
Loc function	Yes
Residual heat indicator	Yes
Cool function	No
Motor, type	Brush motor
Heating element	Ceramic heating element
Mains power supply	220 – 230 V / 50 – 60 Hz
Function, hanger	Yes

Restart protection	Yes
Temperature scanner	Yes
Thermal cut-out	Yes
Thermostat	Yes
Nozzle receiver, type	34
Cord length	3 m
Dimensions (L x W x H)	253 x 87 x 200 mm
PU1, net weight	1,08 kg
Manufacturer's Warranty	1 year
PU1, EAN	4007841089672
Scope of delivery	incl. reflector nozzle, wide jet nozzle 50mm, reducing nozzle 9mm, shrink hose 1.6-9.5
Output	2300 W
Product category	Hot air tool

Accessories

EAN 4007841 014919

Temperature scanner HL Scan

<https://www.steinell.de>

Subject to technical modifications

01.2025 Page 1 from 2

HM 2320 E

Case
EAN 4007841 089672
Article number 089672



Accessories

EAN 4007841 053963	Hot Air Tool Guard Cage HL 1820 S - HG 2320 E
EAN 4007841 074616	Soldering reflector nozzle 10 mm
EAN 4007841 009571	Reduction nozzle 6 mm
EAN 4007841 070618	Reduction nozzle 9 mm
EAN 4007841 070717	Reduction nozzle 14 mm
EAN 4007841 074715	Wide-slit nozzle
EAN 4007841 010287	Fast welding nozzle 5mm - for 5mm rd. noz.
EAN 4007841 068035	Adapter nozzle