



## PM - PMC

**FILTERING DEGREE:**  
 1 micron + residual oil 0.5 mg/m<sup>3</sup>  
 To install after the dryer or QM filters.  
 This filter, following cut-off and coalescence principles, forces the oily fluid particles to collide and build larger drops.

Suitable for painting jobs.

FILTERS								
CODE	TYPE	l/min.	m <sup>3</sup> /h	c.f.m.	bar	p.s.i.	G	Ø x H (cm)
	<b>PM 05</b>	417	25	15	16	232	1/4"	10 x 22
	<b>PM 10</b>	833	50	30	16	232	3/8"	10 x 22
	<b>PM 18</b>	1667	100	59	16	232	1/2"	10 x 25
	<b>PM 30</b>	2.500	150	88	16	232	3/4"	12 x 29
	<b>PM 34</b>	3.333	200	118	16	232	3/4"	12 x 36
	<b>PM 50</b>	5.000	300	176	16	232	1" 1/4	12 x 45
	<b>PM 72</b>	8.333	500	294	16	232	1" 1/4	12 x 48
	<b>PM 95</b>	10.000	600	353	16	232	1" 1/2	16 x 62
	<b>PM 125</b>	14.183	851	500	16	232	2"	16 x 62
	<b>PM 165</b>	20.167	1.210	712	16	232	2"	16 x 69
	<b>PM 220</b>	25.333	1.520	895	16	232	2" 1/2	19 x 72
	<b>PM 280</b>	30.333	1.820	1.070	16	232	3"	19 x 86
	<b>PM 350</b>	37.000	2.220	1.305	16	232	3"	19 x 92
	<b>PM 440</b>	45.000	2.700	1.588	16	232	3"	19 x 106

CARTRIDGES	
CODE	TYPE
<b>9058227</b>	<b>PMC 05</b>
<b>9058228</b>	<b>PMC 10</b>
<b>9058229</b>	<b>PMC 18</b>
<b>9058230</b>	<b>PMC 30</b>
<b>9058231</b>	<b>PMC 34</b>
<b>9058232</b>	<b>PMC 50</b>
<b>9058233</b>	<b>PMC 72</b>
<b>9058234</b>	<b>PMC 95</b>
<b>9058235</b>	<b>PMC 125</b>
<b>9058236</b>	<b>PMC 165</b>
<b>9058238</b>	<b>PMC 220</b>
<b>9058239</b>	<b>PMC 280</b>
<b>9058240</b>	<b>PMC 350</b>
<b>9058241</b>	<b>PMC 440</b>