



## HM - HMC

**FILTERING DEGREE:**  
 0.01 micron + residual oil 0.01 mg/m<sup>3</sup>  
 To install after the QM and PM filters.  
 This filter differs from the PM filter only  
 for its filtering degree. This filter pro-  
 vides a supply  
 of air with 0.01 mg/m<sup>3</sup> residual oil con-  
 tent.

Suitable for water-based painting jobs.

FILTRI   FILTERS									CARTRIDGES	
CODE	TYPE	l/min.	m <sup>3</sup> /h	c.f.m.	bar	p.s.i.	G	Ø x H (cm)	CODE	TYPE
	<b>HM 05</b>	417	25	15	16	232	1/4"	10 x 22	<b>9058257</b>	<b>HMC 05</b>
	<b>HM 10</b>	833	50	30	16	232	3/8"	10 x 22	<b>9058258</b>	<b>HMC 10</b>
	<b>HM 18</b>	1667	100	59	16	232	1/2"	10 x 25	<b>9058259</b>	<b>HMC 18</b>
	<b>HM 30</b>	2.500	150	88	16	232	3/4"	12 x 29	<b>9058260</b>	<b>HMC 30</b>
	<b>HM 34</b>	3.333	200	118	16	232	3/4"	12 x 36	<b>9058261</b>	<b>HMC 34</b>
	<b>HM 50</b>	5.000	300	176	16	232	1" 1/4	12 x 45	<b>9058262</b>	<b>HMC 50</b>
	<b>HM 72</b>	8.333	500	294	16	232	1" 1/4	12 x 48	<b>9058263</b>	<b>HMC 72</b>
	<b>HM 95</b>	10.000	600	353	16	232	1" 1/2	16 x 62	<b>9058264</b>	<b>HMC 95</b>
	<b>HM 125</b>	14.183	851	500	16	232	2"	16 x 62	<b>9058265</b>	<b>HMC 125</b>
	<b>HM 165</b>	20.167	1.210	712	16	232	2"	16 x 69	<b>9058266</b>	<b>HMC 165</b>
	<b>HM 220</b>	25.333	1.520	895	16	232	2" 1/2	19 x 72	<b>9058268</b>	<b>HMC 220</b>
	<b>HM 280</b>	30.333	1.820	1.070	16	232	3"	19 x 86	<b>9058269</b>	<b>HMC 280</b>
	<b>HM 350</b>	37.000	2.220	1.305	16	232	3"	19 x 92	<b>9058270</b>	<b>HMC 350</b>
	<b>HM 440</b>	45.000	2.700	1.588	16	232	3"	19 x 106	<b>9058271</b>	<b>HMC 440</b>