



HM - HMC

FILTERING DEGREE:
 0.01 micron + residual oil 0.01 mg/m³
 To install after the QM and PM filters.
 This filter differs from the PM filter only
 for its filtering degree. This filter pro-
 vides a supply
 of air with 0.01 mg/m³ residual oil con-
 tent.

Suitable for water-based painting jobs.

FILTRI FILTERS									CARTRIDGES	
CODE	TYPE	l/min.	m ³ /h	c.f.m.	bar	p.s.i.	G	Ø x H (cm)	CODE	TYPE
	HM 05	417	25	15	16	232	1/4"	10 x 22	9058257	HMC 05
	HM 10	833	50	30	16	232	3/8"	10 x 22	9058258	HMC 10
	HM 18	1667	100	59	16	232	1/2"	10 x 25	9058259	HMC 18
	HM 30	2.500	150	88	16	232	3/4"	12 x 29	9058260	HMC 30
	HM 34	3.333	200	118	16	232	3/4"	12 x 36	9058261	HMC 34
	HM 50	5.000	300	176	16	232	1" 1/4	12 x 45	9058262	HMC 50
	HM 72	8.333	500	294	16	232	1" 1/4	12 x 48	9058263	HMC 72
	HM 95	10.000	600	353	16	232	1" 1/2	16 x 62	9058264	HMC 95
	HM 125	14.183	851	500	16	232	2"	16 x 62	9058265	HMC 125
	HM 165	20.167	1.210	712	16	232	2"	16 x 69	9058266	HMC 165
	HM 220	25.333	1.520	895	16	232	2" 1/2	19 x 72	9058268	HMC 220
	HM 280	30.333	1.820	1.070	16	232	3"	19 x 86	9058269	HMC 280
	HM 350	37.000	2.220	1.305	16	232	3"	19 x 92	9058270	HMC 350
	HM 440	45.000	2.700	1.588	16	232	3"	19 x 106	9058271	HMC 440