



CM - CMC

OIL RESIDUAL:
0.003 mg/m³ + oil vapors and odours
To install after the HM filter.
Where applications require oil free, vaporless and odourless air, the activated carbon filter eliminates odours and vapours using the absorption technique.

Recommended for packing applications in pharmaceutical and food industries.

FILTERS									CARTRIDGES	
CODE	TYPE	l/min.	m ³ /h	c.f.m.	bar	p.s.i.	G	Ø x H (cm)	CODE	TYPE
	CM 05	417	25	15	16	232	1/4"	10 x 22	9058287	CMC 05
	CM 10	833	50	30	16	232	3/8"	10 x 22	9058288	CMC 10
	CM 18	1667	100	59	16	232	1/2"	10 x 25	9058289	CMC 18
	CM 30	2.500	150	88	16	232	3/4"	12 x 29	9058290	CMC 30
	CM 34	3.333	200	118	16	232	3/4"	12 x 36	9058291	CMC 34
	CM 50	5.000	300	176	16	232	1" 1/4	12 x 45	9058292	CMC 50
	CM 72	8.333	500	294	16	232	1" 1/4	12 x 48	9058293	CMC 72
	CM 95	10.000	600	353	16	232	1" 1/2	16 x 62	9058294	CMC 95
	CM 125	14.183	851	500	16	232	2"	16 x 62	9058295	CMC 125
	CM 165	20.167	1.210	712	16	232	2"	16 x 69	9058296	CMC 165
	CM 220	25.333	1.520	895	16	232	2" 1/2	19 x 72	9058298	CMC 220
	CM 280	30.333	1.820	1.070	16	232	3"	19 x 86	9058299	CMC 280
	CM 350	37.000	2.220	1.305	16	232	3"	19 x 92	9058300	CMC 350
	CM 440	45.000	2.700	1.588	16	232	3"	19 x 106	9058301	CMC 440

Tашев Галвинг
www.tashevgalving.com