

COMMERCIAL MODEL ID	SXUP400PCE
PRODUCT CODE	51766
EAN BARCODE	8016287517669
Description of pump	Plastic submersible pump with floater switch and top water discharge for clean water
Rated Power	400W
Horse Power	1/3HP
Country of origin	China
Motor	
Motor type	Induction
Motor winding	Aluminum wire
Diameter of Stator (mm)	90
Stator height (mm)	32
Resistenze (W)	40.27Ω(20°C) 35.02Ω(20°C)
Pole - Speed motor	2 pole - 2800Rpm
Phase	Single phase
Protection type	IPX8
Insulation class	F
Thermal Protector	YES
Rated Power	400W
Voltage & frequency	230V/50Hz
Operation conditions	
Inlet Water temperature	35°C
Max. Grain size inlet	Ø 5 mm
Min. suction water level	5 mm
Max. delivery head	8 m

Max. Flow	9000 l/h
Max. Submersion depth	7m
Max. Suction Height	/
Max. working pressure	0.8bar
Fittings diameters	G1"G1-1/4"G1-1/2"
<u>Materials</u>	
Power cable specification	H05RN-F 3G0.75mm ²
Power cord length	10m
Seal type	Mechanical seal
Material of mechanical seal	Carbon - ceramic
Material of motor shaft	AISI 420
Material of stator	Q195
<u>Unit dimensions</u>	
Net Weight	4.3kg
LxWxH	217*167*312mm
Pressure tank volume	/
Master carton box (Yes / No)	Yes
Drop test applicable (Yes / No)	NO
<u>Logistic details</u>	
Color box size (cm)	24X19X36
Pieces per Neutral Master-Carton	2 pcs/master
Mastercarton box size/2-4PCS	400x260x380mm
Qty of 20'GP (without pallet)	1488
Qty of 40'GP (without pallet)	3060
Qty of 40'HQ (without pallet)	3570
Qty of PLT 80x120x220 cm	45x2 405Kg
<u>Functionalities</u>	
Built-in filter	/
Automatic switch	/
User manual	Yes
4 color gift box	Yes
Polyfoam inner packing	No
<u>Accessories</u>	
Suction hose w plastic fittings (4m)	/
Suction hose w brass fittings (7m)	/
Filter 1L	/
Filter 2L	/
Automatic switch	/
Delivery set	Yes