

228/KIT

Diesel Kit 12 Volt



Kit to transfer diesel. Without suction rubber hose with filter, exit rubber hose and nozzle. Self-priming, rotating, electric vane pump, equipped with by-pass valve and filter. Brush motor, DC, low tension with intermittent cycle, closed type in protecti

Allowed fluids	DIESEL
Color	RED
DIM Height	12 cm
DIM Length	23 cm
DIM Width	12 cm
Duty cycle	30 min
Entry diameter	3/4"
Exit diameter	3/4"
Flow-rate	40 LT/MIN
Material	STEEL - BODY IN CAST IRON, VANES IN PLASTIC RESIN, ROTOR IN STEEL
Maximum suction height	2-3 mt
Not allowed fluids	GASOLINE, INFLAMMABLE LIQUIDS WITH PM<55°C, LIQUIDS WITH VISCOSITY >20 Cst, WATER, FOOD LIQUIDS, CORROSIVE CHEMICAL FLUIDS AND SOLVENTS
Notes	The installation of a foot valve (art. 734/A) is recommended to prevent the emptying of the suction tube
Operating temperature	-20 ÷ 60 °C
Origin	IMPORT TYPE
Regulations	2006/42/CE & 2006/95/CE & 2004/108/CE
Single packing	CARTON BOX
Thread	3/4"
Vertical lift	12 mt
Voltage	12 V
Working	ELECTRIC