

229/F/KIT

Diesel pump 220 Volt with accessories



65 lt/min. To transfer diesel. With rubber suction hose and exit rubber hose with nozzle. Self-priming, volumetric, rotating, electric vane pump, equipped with by-pass valve and filter. Asynchronous motor, single-phase, 2 poles, closed type (protection cl

Allowed fluids	DIESEL
DIM Height	20CM
DIM Length	25 CM
DIM Width	15 CM
Entry diameter	1"
Exit diameter	1"
Flow-rate	65 LT/MIN
Material	STEEL - BODY IN CAST IRON, VANES IN PLASTIC RESIN, ROTOR IN STEEL
Maximum suction height	2-3 mt
Multiple packing	CARTON BOX
Not allowed fluids	GASOLINE, INFLAMMABLE LIQUIDS WITH PM<55°C, LIQUIDS WITH VISCOSITY >20 Cst, WATER, FOOD LIQUIDS, CORROSIVE CHEMICAL FLUIDS AND SOLVENTS
Notes	The installation of a foot valve (art. 734/A) is recommended to prevent the emptying of the suction tube
Operating temperature	-20 ÷ 60 °C
Origin	MADE IN ITALY
Power	370 W
Regulations	2006/42/CE & 2006/95/CE & 2004/108/CE
Single packing	CARTON BOX
Thread	1"
Vertical lift	23 mt
Voltage	220 V
Working	ELECTRIC