

Помпа бензинова за поливни води Honda WX 15



Length	12.8 in (325 mm)
Width	10.8 in (275 mm)
Height	With rubber feet: 14.8 in (375 mm)
Dry mass [weight]	20 lbs (9 kg)

Engine design and performance

Model	GXH50T	
Engine type	4-stroke, overhead valve, single cylinder	
Displacement [bore × stroke]	3.0 cu-in (49.4 cm ³) [1.65 × 1.42 in (41.8 × 36.0 mm)]	
Engine oil capacity	8 oz (0.25 L)	
Fuel tank capacity	0.203 US gal (0.77 L)	
Cooling system	Forced air	
Ignition system	Transistor magneto	
PTO shaft rotation	Counterclockwise	

Tune up

Spark plug gap	0.024–0.028 in (0.60–0.70 mm)	See page 36.
Idle speed	2,500 ± 200 rpm	
Valve clearance (cold)	Intake: 0.08 ± 0.02 mm Exhaust: 0.11 ± 0.02 mm	See shop manual.
Other specifications	No other adjustments needed.	

Pump

Suction port diameter	1.6 in (40 mm)
Discharge port diameter	1.6 in (40 mm)
Total head (maximum)	131 ft (40 m)
Suction head (maximum)	26 ft (8 m)
Discharge capacity (maximum)	63.4 US gal (240 L) per minute
Self-priming time	120 seconds at 16.4 ft (5 m)

